

FINAL REPORT
JUNE 1995

REPORT NO. 95-12

M1077 FLATRACK
VALIDATION TESTS

19960726 127

Prepared for:
U.S. Army Tank-automotive and
Armaments Command
ATTN: SFAE-TWV-PLS
Warren, MI 48397-5000


Distribution Unlimited



VALIDATION ENGINEERING DIVISION
SAVANNA, ILLINOIS 61074-9639

THIS QUANTITY IS UNCLASSIFIED

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

AVAILABILITY NOTICE

A copy of this report will be furnished each attendee on automatic distribution. Additional copies or authority for reprinting may be obtained by written request from Director, U.S. Army Defense Ammunition Center and School, ATTN: SIOAC-DEV, Savanna, IL 61074-9639.

DISTRIBUTION INSTRUCTIONS

Destroy this report when no longer needed. Do not return.

Citation of trade names in this report does not constitute an official endorsement.

The information contained herein will not be used for advertising purposes.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			UNLIMITED		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) 95-12			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION U.S. Army Defense Ammunition Center and School		6b. OFFICE SYMBOL (if applicable) SIOAC-DEV	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) ATTN: SIOAC-DEV Savanna, IL 61074-9639			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION U.S. Army Tank-automotive and Armaments Command		8b. OFFICE SYMBOL (if applicable) SFAE-TWV-PLS	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code) ATTN: SFAE-TWV-PLS Warren, MI 48397-5000			10. SOURCE OF FUNDING NUMBERS	10. SOURCE OF FUNDING NUMBERS	
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
					WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) M1077 Flatrack Validation Tests					
12. PERSONAL AUTHOR(S) A. C. McIntosh, Jr.					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) 1995 June	
15. PAGE COUNT					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP			
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>The U.S. Army Defense Ammunition Center and School (USADACS), Validation Engineering Division (SIOAC-DEV), was tasked by U.S. Army Tank-automotive and Armaments Command (TACOM) to test a newly-fabricated M1077 flatrack. This particular flatrack has one International Organization for Standardization (ISO) fitting welded at the outer limits of the manufacturing drawings tolerances. The flatrack was loaded with 155MM Separate Loading Projectiles (SLPs) and subjected to rail impact tests at 4, 6, and 8.1 mph and 8.1 mph in reverse in three different transportation modes. The transportation modes are as follows: Container-on-Flatcar (COFC), Trailer-on-Flatcar (TOFC), and cabled to a standard wooden deck flatcar with 5/8-inch cables. Following transportation testing, the SLP load was removed and the corner fitting was inspected for cracks and breaks. This report contains details of the tests conducted.</p>					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL JEROME H. KROHN			22b. TELEPHONE (Include Area Code) 815-273-8929		22c. OFFICE SYMBOL SIOAC-DEV

U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL
VALIDATION ENGINEERING DIVISION
SAVANNA, IL 61074-9639

REPORT NO. 95-12

M1077 FLATRACK VALIDATION TESTS

TABLE OF CONTENTS

PART	PAGE NO.
1. INTRODUCTION	1-1
A. BACKGROUND	1-1
B. AUTHORITY	1-1
C. OBJECTIVE	1-1
D. CONCLUSION	1-2
E. RECOMMENDATION	1-2
2. ATTENDEES	2-1
3. TEST PROCEDURES	3-1
4. TEST RESULTS	4-1
5. PHOTOGRAPH	5-1
6. DRAWING	6-1

PART 1

INTRODUCTION

A. BACKGROUND. The U.S. Army Defense Ammunition Center and School (USADACS), Validation Engineering Division (SIOAC-DEV), was tasked by U.S. Army Tank-automotive and Armaments Command (TACOM) to test a newly-fabricated M1077 flatrack. This particular flatrack has one International Organization for Standards (ISO) fitting welded at the outer limits of the manufacturing tolerances. This flatrack was tested to the most severe transportation environment; namely, movement by railcar, to the test criteria specified in Transportability Testing Procedures, TP-94-01, July 1994.

B. AUTHORITY. These tests were conducted IAW mission responsibilities delegated by U.S. Army Armament, Munitions and Chemical Command (AMCCOM), Rock Island, IL 61299-6000. Reference is made to Change 4, 4 October 1974, to AR 740-1, 23 April 1971, Storage and Supply Operations; AMCCOMR 10-17, 13 January 1986, Mission and Major Functions of USADACS.

C. OBJECTIVE. The flatrack was loaded with 155MM Separate Loading Projectiles (SLPs) and subjected to rail impact tests at 4, 6, and 8.1 mph and 8.1 mph in reverse in three different transportation modes. The types of railway equipment utilized are as follows: Container-on-flatcar (COFC), Trailer-on-flatcar (TOFC), and cabled to a standard wooden deck flatcar with 5/8-inch cables (steel wire rope). Following transportation testing, the SLP load was removed and the corner fittings inspected for cracks and breaks.

D. CONCLUSION.

1. The M1077 flatrack tested on the three types of railway equipment remained intact without any component failure; however, following rail impact of the flatrack cabled to a the standard flatcar, it was noted that the flatrack tiedown rings were deformed. It is estimated that the rings experienced dynamic loads in excess of 35,000 pounds of tension which caused the permanent deformation.

2. Slings had to be used to move the flatrack both onto and off of the railcars using the tiedown rings. The position of the forward tiedown rings (on the hook side of the platform) does not allow the load to be picked up without the use of a spreader bar. Without a spreader bar, the flatrack accessory boxes are easily damaged by cables of the sling. Spreader bars are not available at all installations.

E. RECOMMENDATION. Strengthen the flatrack tiedown rings and reposition the forward tie-downs to the outside of the flatrack so that the flatrack can be slung without the use of a spreader bar.

PART 2

22 - 23 MAY 1995

ATTENDEES

A.C. McIntosh, Jr.
General Engineer
DSN: 585-8989
815-273-8989

David V. Valant
Electronics Technician
DSN: 585-8988
815-273-8988

Jerome H. Krohn
Supervisory General Engineer
DSN: 585-8908
815-273-8908

John D. Simons
Industrial Engineer
DSN: 585-8074
815-273-8074

Gregory Willis
Industrial Engineer
DSN: 585-8075
815-273-8075

Director
U.S. Army Defense Ammunition Center
and School
ATTN: SIOAC-DEV
Savanna, IL 61074-9639

Director
U.S. Army Defense Ammunition Center
and School
ATTN: SIOAC-DEV
Savanna, IL 61074-9639

Director
U.S. Army Defense Ammunition Center
and School
ATTN: SIOAC-DEV
Savanna, IL 61074-9639

Director
U.S. Army Defense Ammunition Center
and School
ATTN: SIOAC-DET
Savanna, IL 61074-9639

Director
U.S. Army Defense Ammunition Center
and School
ATTN: SIOAC-DET
Savanna, IL 61074-9639

PART 3

TEST PROCEDURES

A. Test procedures were extracted from TP-94-01, Transportability Testing Procedures, July 1994, for validating tactical vehicles and outloading procedures used for shipping munitions by intermodal freight containers, commercial or tactical truck, or trailer or railcar.

B. The M1077 test load was prepared using the same blocking and bracing methods specified in the tiedown procedures proposed for use with munitions (see Part 6). The M1077 flatracks used in these tests were inspected to ensure their adequacy for munitions transport. Items used to build the load were inert (nonexplosive). The weight and physical characteristics of the load configuration were identical to the live (explosive) ammunition provided for in the tiedown procedure; i.e., weights, physical dimensions, center of gravity (CG), materials, etcetera.



C. Rail impact tests conducted for this load are as follows:

1. COFC.
2. TOFC.
3. Standard flatcar.

D. Test Method No. 1. The inertly-loaded M1077 flatrack was loaded onto a COFC, was loaded on a container chassis secured to a TOFC, and was loaded on and secured to a conventional friction draft gear flatcar. Equipment needed to perform the test included the specimen (hammer) car, five empty railroad cars connected together to serve as an anvil, and a railroad locomotive. These anvil cars were positioned on a level section of track with air and hand brakes set and with draft gears compressed. The locomotive unit pulled the specimen car several hundred yards away from the anvil cars, pushed the specimen car toward the anvil at a

predetermined speed, then disconnected from the specimen car approximately 50 yards away from the anvil cars which allowed the specimen car to roll freely along the track until it struck the anvil. This constituted an impact. Impacting was accomplished at speeds of 4, 6, and 8.1 mph and at a speed of 8.1 mph in reverse. The 4 mph and 6 mph impact speeds were approximate; the 8.1 mph speed was minimum. Impact speeds were determined by using an electronic counter to measure the time it takes for the specimen car to traverse an 11-foot distance immediately prior to contact with the anvil cars (see Figure 1).

ASSOCIATION OF AMERICAN RAILROADS (AAR) STANDARD TEST PLAN



SPECIMEN CAR
IS RELEASED BY
SWITCH ENGINE TO

ATTAIN: IMPACT NO. 1 @ 4 MPH
IMPACT NO. 2 @ 6 MPH
IMPACT NO. 3 @ 8.1 MPH

THEN THE CAR IS REVERSED AND
RELEASED BY SWITCH ENGINE TO

ATTAIN: IMPACT NO 4. @ 8.1 MPH

5 BUFFER CARS (ANVIL) WITH DRAFT GEAR
COMPRESSED AND AIR BRAKES IN A SET
POSITION

ANVIL CARS TOTAL WT 250,000 LBS (APPROX)

FIGURE 1

PART 4
TEST RESULTS

RAIL IMPACT DATA

TEST NO. 1

DATE: 22 May 1995

TEST SPECIMEN: M1077 A-frame Flatrack with 155MM Separate Loading Projectiles (SLPs).

COFC NO.: TTWX 979262

LT. WT.: 80,500 pounds

CONTAINER TYPE: M1077 Flatrack NO.: 3265

WT.: 3,200 pounds

LOAD TYPE: 155MM SLPs

WT.: 32,572 pounds

TOTAL SPECIMEN WT.: 116,272 pounds

BUFFER CAR (5 CARS) WT.: 250,000 pounds

<u>IMPACT NO.</u>	<u>END STRUCK</u>	<u>VELOCITY (MPH)</u>	<u>REMARKS</u>
1	Forward	4.44	Load compacted 1/2-inch.
2	Forward	6.51	No visible damage.
3	Forward	8.61	Dunnage broken at knots in lumber.
4	Reverse	9.26	Additional broken dunnage.

Notes:

1. The COFC had cushioned draft gear. This office could not obtain a COFC that had friction draft gear from our supplier.
2. The Forward impact direction means that the flatrack bail bar was facing the direction of impact.

RAIL IMPACT DATA

TEST NO. 2

DATE: 22 May 1995

TEST SPECIMEN: M1077 A-frame Flatrack with 155MM SLPs.

TOFC NO.: TTX 600585

LT. WT.: 75,600 pounds

CHASSIS NO.: 5394

WT: 6,100 pounds

CONTAINER TYPE: M1077 Flatrack NO: 3265

WT.: 3,200 pounds

LOAD TYPE: 155MM SLPs.

WT.: 32,572 pounds

TOTAL SPECIMEN WT.: 122,372 pounds

BUFFER CAR (5 CARS) WT.: 250,000 pounds

<u>IMPACT</u>	<u>END STRUCK</u>	<u>COUPLER</u>	VELOCITY	<u>REMARKS</u>
			<u>(MPH)</u>	
1	Forward	2,400,000	4.62	Load compacted.
2	Forward	3,200,000	6.64	Chains tightened.
3	Forward	4,200,000	8.70	No load movement.
4	Reverse	4,500,000	8.37	Load moved 2 inches at center.

Notes:

1. The TOFC had friction draft gear which accounts for higher coupler forces.
2. The Forward impact direction means that the flatrack bail bar was facing the direction of impact.

RAIL IMPACT DATA

TEST NO.: 3

DATE: 22 May 1995

TEST SPECIMEN: M1077 A-frame Flatrack with 155MM SLPs.

FLATCAR NO.: BN 615005

LT. WT.: 47,400 pounds

CONTAINER TYPE: M1077 Flatrack NO.: 3265

WT.: 3,200 pounds

LOAD TYPE: 155MM SLPs.

WT.: 32,572 pounds

TOTAL SPECIMEN WT.: 83,172 pounds

BUFFER CAR (5 CARS) WT.: 250,000 pounds


<u>IMPACT</u>	<u>END STRUCK</u>	<u>COUPLER</u>	<u>VELOCITY</u> <u>(MPH)</u>	<u>REMARKS</u>
1	Forward	1,850,000	4.93	Load compacted.
2	Forward	3,500,000	6.31	No visible damage.
3	Forward	5,500,000	8.52	Rear cables broke, elongated tiedown rings.
4	Reverse	5,200,000	8.62	Broken dunnage, tiedown ring deformed.

Notes:

1. This flatcar had friction draft gear.
2. The Forward impact direction means that the flatrack bail bar was facing the direction of impact.

PART 5

PHOTOGRAPH



U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL -
SAVANNA, IL

AO317-SCN95-134-1949. This photo shows the M1077 flatrack cabled to a friction draft gear flatcar which was rail impact tested at 4, 6, and 8.1 mph and 8.1 mph in reverse.

PART 6

DRAWING



LOADING AND TIEDOWN PROCEDURES FOR CONVENTIONAL AMMUNITION ITEMS LOADED ON THE PALLETIZED LOADING SYSTEM (PLS) A-FRAME FLATRACK (M1077), AND/OR THE ISO COMPATIBLE PLS FLATRACK (IPF) (M1), FOR RAPID DEPLOYMENT BY RAIL AND SHIP

INDEX

<u>ITEM</u>	<u>PAGE(S)</u>
GENERAL NOTES AND MATERIAL SPECIFICATIONS - - - - -	2
LOADING PROCEDURES AND ITEMIZED INDEX - - - - -	3
LOADS ON M1 FLATRACK - - - - -	4-21
LOADS ON A-FRAME FLATRACK - - - - -	22-35
DETAILS - - - - -	36-58

- THE PROCEDURES DEPICTED WITHIN THIS DRAWING ARE FOR TRANSPORTING CONVENTIONAL AMMUNITION ITEMS LOADED ON THE PALLETIZED LOADING SYSTEM (PLS) A-FRAME AND/OR M1 FLATRACKS, BY RAIL AND/OR SHIP. HOWEVER, THEY MAY ALSO BE USED FOR ON AND/OR OFF HIGHWAY MOVEMENT, IF DESIRED.

DEPARTMENT OF ARMY DRAWING

	DRAFTSMAN	TECHNICIAN	ENGINEER
	B. LEONARD		J. SIMONS
	VALIDATION ENGINEERING DIVISION	TRANSPORTATION ENGINEERING DIVISION	LOGISTICS ENGINEERING OFFICE
OCTOBER 1994			
DRAWING NUMBER	APPROVED BY ORDER OF COMMANDING GENERAL, U.S. ARMY MATERIEL COMMAND 		
DA-114	U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL		

DO NOT SCALE

GENERAL NOTES

- A. THIS DOCUMENT HAS BEEN PREPARED AND ISSUED IN ACCORDANCE WITH AR-740-1.
- B. THIS DRAWING COVERS PROCEDURES APPLICABLE TO THE TRANSPORT OF CONVENTIONAL AMMUNITION ITEMS, SECURED ON THE PALLETIZED LOADING SYSTEM (PLS) M1077 A-FRAME AND/OR M1 IPF FLATRACK, FOR RAPID DEPLOYMENT BY RAIL AND SHIP. THESE PROCEDURES MAY ALSO BE USED FOR ON AND/OR OFF HIGHWAY TRANSPORT. IF THE PLANNED METHOD OF TRANSPORT IS ONLY ON AND/OR OFF HIGHWAY, USE THE LOADING AND TIEDOWN PROCEDURES DEPICTED IN AMC DRAWING 19-48-4903-CA1704.
- C. DEPICTED PROCEDURES APPLY TO M1077 A-FRAME FLATRACKS HAVING AN ALL METAL CARGO DECK AREA 19'-0" LONG BY 7'-6-3/4" WIDE, EQUIPPED WITH ELEVEN TIEDOWN ANCHORS ON EACH SIDE AND FOUR ON EACH END. THE EMPTY FLATRACK WEIGHT IS 3,200 POUNDS AND THE LOAD CAPACITY IS 33,000 POUNDS. THE DEPICTED PROCEDURES ALSO APPLY TO THE M1 FLATRACK WHICH HAS A WOOD AND METAL CARGO DECK AREA 18'-6" LONG BY 7'-6-1/2" WIDE, EQUIPPED WITH ELEVEN TIEDOWN ANCHORS ON EACH SIDE. THE EMPTY FLATRACK WEIGHT IS 7,500 POUNDS AND THE LOAD CAPACITY IS 28,750 POUNDS.
- D. ALL LOADS SHOWN HEREIN ARE TYPICAL AND ARE BASED ON TESTED PROCEDURES FOR THE M1077 AND/OR THE M1 FLATRACKS WITH MAXIMUM WEIGHT LOADS, LOADED ON THE PLS VEHICLE AND TRAILER, WHICH WERE SECURED TO FLAT CARS. EACH LOADED FLATRACK WAS ALSO SECURED DIRECTLY TO THE FLOOR OF THE FLAT CAR. COMBINATIONS OF PROCEDURES MAY BE USED ON THE FLATRACKS, HOWEVER, THE APPROVED METHODS SPECIFIED HEREIN MUST BE FOLLOWED AS CLOSELY AS POSSIBLE.
- E. BECAUSE OF THE FACT THAT ALL LOADS SHOWN HEREIN ARE TYPICAL IT IS MOST LIKELY THAT THE ACTUAL QUANTITY TO BE TRANSPORTED WILL NOT BE DEPICTED. IN ORDER TO MAINTAIN SIMILARITY FROM ONE LOAD TO ANOTHER, INSTALLATIONS WHICH MAKE MULTIPLE SHIPMENTS OF THE SAME ITEM, SHOULD MAKE AN ACTUAL PENCIL SKETCH OF THE LOAD, USING THE VARIOUS TYPICAL LOADS AND PROCEDURES SHOWN HEREIN FOR GUIDANCE. THE SKETCH WOULD BE ADVANTAGEOUS FOR MAXIMUM LOADS USING A MINIMUM QUANTITY OF STEEL STRAPPING AND DUNNAGE ASSEMBLIES.
- F. PROCEDURES DEPICTED HEREIN ARE TYPICAL IN NATURE RELATIVE TO ITEM LOCATION ON THE FLATRACK AND THE QUANTITIES SHOWN. ITEM LOCATION AND QUANTITIES OF THE DESIGNATED ITEM MAY BE VARIED TO SATISFY OPERATIONAL REQUIREMENTS, PROVIDED LOADING AND TIEDOWN PROCEDURES SPECIFIED HEREIN ARE RETAINED.
- G. CONVERSION TO METRIC EQUIVALENTS: DIMENSIONS WITHIN THIS DOCUMENT ARE EXPRESSED IN INCHES, AND WEIGHTS ARE EXPRESSED IN POUNDS. WHEN NECESSARY THE METRIC EQUIVALENTS MAY BE COMPUTED ON THE BASIS OF ONE INCH EQUALS 25.4MM AND ONE POUND EQUALS 0.454KG.
- H. DUNNAGE LUMBER SPECIFIED THROUGHOUT THIS PROCEDURAL DRAWING IS OF NOMINAL SIZE. FOR EXAMPLE, 2" X 4" MATERIAL IS ACTUALLY 1-1/2" THICK BY 3-1/2" WIDE AND 2" X 6" MATERIAL IS ACTUALLY 1-1/2" THICK BY 5-1/2" WIDE.

(CONTINUED AT RIGHT)

(GENERAL NOTES CONTINUED)

- J. NOTICE: A STAGGERED NAILING PATTERN WILL BE USED WHEREVER POSSIBLE WHEN NAILS ARE DRIVEN INTO JOINTS OF DUNNAGE ASSEMBLIES. ALSO, A STAGGERED NAILING PATTERN WILL BE USED WHEN LAMINATING DUNNAGE.
- K. CAUTION: NAILING THROUGH ANY PORTION OF AMMUNITION PACKAGES AS A MEANS TO SUPPORT THE BRACING OR ANY TYPE OF DUNNAGE IS PROHIBITED. ALL NAILING WILL BE WITHIN THE DUNNAGE, AS SPECIFIED HEREIN.
- L. WHEN 2" STEEL STRAPPING IS SEALED AT AN END-OVER-END LAP JOINT, A MINIMUM OF TWO (2) SEALS, BUTTED TOGETHER, WITH TWO (2) PAIR OF CRIMPS PER SEAL MUST BE USED.
- M. WHEN 3/4" AND/OR 1-1/4" STEEL STRAPPING IS SEALED AT AN END-OVER-END LAP JOINT, USE ONE SEAL WITH TWO PAIR OF CRIMPS.
- N. TO ACHIEVE A TIGHTLY BLOCKED LOAD, A STRUT WILL BE CUT APPROXIMATELY 1/4" TO 3/8" LONGER THAN THE MEASURED DISTANCE BETWEEN THE STRUT BEARING AREAS ON THE TWO CENTER GATES. MEASUREMENTS FOR STRUT LENGTHS NEED TO BE ACCOMPLISHED AT SEVERAL PLACES DURING THE BLOCKING AND BRACING PROCESS. CARE MUST BE EXERCISED WHEN MEASURING FOR AND INSTALLING STRUTS. THE SPECIFIED APPROXIMATE DIMENSION FOR A STRUT LENGTH MAY BE ADJUSTED, AS NECESSARY, TO PROVIDE FOR A TIGHTLY BLOCKED LOAD. ONE END OF THE STRUT WILL BE POSITIONED AT ITS BEARING AREA JUST ABOVE THE STRUT LEDGER ON ONE GATE. THE OTHER END, WHICH CAN BE BEVELED ON THE LOWER CORNER IF DESIRED, WILL THEN BE DRIVEN DOWNWARD UNTIL IT CONTACTS THE STRUT LEDGER ON THE OTHER GATE. EACH END OF THE STRUT WILL BE TOENAILED TO THE ADJACENT CENTER GATE, AS SPECIFIED WITHIN THE KEY NUMBERS FOR A LOAD, IN SUCH A MANNER SO THAT AS NEARLY AS PRACTICAL EQUAL LENGTHS OF A NAIL ARE EMBEDDED IN THE STRUT AND IN THE VERTICAL PIECE OF THE CENTER GATE.
- O. WHEN REFERRING TO THE PALLET UNIT LENGTH OR UNIT WIDTH, THE 40" OR 35" DIMENSION OF THE PALLET BASE CONSTITUTES THE PALLET UNIT LENGTH AND THE 48" OR 45-1/2" DIMENSION CONSTITUTES THE PALLET UNIT WIDTH. WHEN REFERRING TO THE SKIDDED UNIT LENGTH OR UNIT WIDTH, THE LENGTH OF THE BOXES CONSTITUTES THE WIDTH OF THE SKIDDED UNIT.
- P. ANY REFERENCE TO "PALLET" WITHIN THIS DOCUMENT MEANS PALLET UNIT AND/OR SKIDDED UNIT.
- Q. FOR ADDITIONAL GUIDANCE SEE THE "LOADING PROCEDURES" ON PAGE 3 AND THE "SPECIAL NOTES" ON EACH LOAD PAGE.
- R. SOME OF THE LOADS SHOWN HEREIN MAY CONTAIN EXPLOSIVE INCOMPATIBLE ITEMS. DURING PEACETIME, THE INCOMPATIBLE ITEMS MUST BE TRANSPORTED SEPARATELY TO COMPLY WITH TITLE 49CFR. DURING TIMES OF DECLARED EMERGENCIES, INCOMPATIBLE LOADS MAY BE TRANSPORTED PROVIDING THEY MEET WITH THE REQUIREMENTS OF PROPER DOT EXEMPTION, E.G., DOT-E-3498.
- S. MANY OF THE LOADS CONTAINED HEREIN MAY BE OF A COMBAT CONFIGURED TYPE. SINCE SOME OF THESE COMBAT CONFIGURED LOADS CONTAIN SENSITIVE ITEMS IN SECURITY RISK CATEGORIES, TRANSPORT ON THESE OPEN FLATRACKS OVER CONUS RAIL OR HIGHWAY CANNOT BE ACCOMPLISHED WITHOUT AN APPROPRIATE SECURITY WAIVER, THEREBY ALLOWING DEVIATIONS FROM AR-55-355 AND DOD 5100.76-M REQUIREMENTS.

MATERIAL SPECIFICATIONS


- LUMBER - - - - - : SEE TM 743-200-1 (DUNNAGE LUMBER) AND FED SPEC MM-L-751.
- NAILS - - - - - : FED SPEC FF-N-105; COMMON.
- STRAPPING, STEEL - - : ASTM D3953; FLAT STRAPPING, TYPE 1, HEAVY DUTY, FINISH A, B (GRADE 2), OR C.
- SEAL, STRAP - - - - : ASTM D3953; CLASS H, FINISH A, B (GRADE 2), OR C, DOUBLE NOTCH TYPE, STYLE I, II, OR IV.
- EDGE PROTECTOR - - - : STEEL, FOR 2" STEEL STRAPPING.

LOADING PROCEDURES:

1. PRIOR TO LOADING ITEMS ON THE FLATRACK ASSURE THAT THE DECK IS FREE OF EXCESSIVE AMOUNTS OF DIRT, SAND AND GRAVEL.
2. BEFORE LOADING A PLS FLATRACK WITH AMMUNITION OR EXPLOSIVES, CHECK THE OVERALL CONDITION OF THE FLATRACK TO ENSURE IT IS SERVICEABLE. CHECK FOR CRACKS, BREAKS, DISTORTIONS, OR EXCESSIVE CORROSION WHICH WOULD MAKE USE OF THE FLATRACK UNSAFE. CHECK THE CARGO TIEDOWN ANCHORS AND THE FLATRACK TIEDOWN DEVICES TO ENSURE THEY ARE SERVICEABLE. MAKE SURE THEY ARE NOT CRACKED, BROKEN, BENT, DISTORTED OR EXCESSIVELY CORRODED TO PRECLUDE SAFE USE. GIVE SPECIAL ATTENTION WHILE CHECKING THE LIFTING DEVICE ON THE HOOKUP END OF THE PLS FLATRACK. MAKE SURE THE HOOKUP DEVICE IS NOT CRACKED, BROKEN, WORN, OR DISTORTED TO SUCH AN EXTENT SO AS TO MAKE THE DEVICE UNSERVICEABLE OR UNSAFE TO USE.
3. IF APPLICABLE, CHECK THE END WALL ON THE M1 FLATRACK TO ASSURE THAT IT CAN BE RAISED AND/OR LOWERED WITHOUT DIFFICULTY. FOLLOW THE MANUFACTURER'S STEP-BY-STEP PROCEDURES FOR RAISING AND/OR LOWERING THE END WALL, AS SERIOUS INJURY OR DEATH TO PERSONNEL COULD RESULT DUE TO THE WEIGHT OF THE WALL.
4. BOTH FLATRACKS ARE EQUIPPED WITH ELEVEN TIEDOWN ANCHORS ALONG EACH SIDE. THE TIEDOWN ANCHORS AT EACH END AND IN THE CENTER HAVE A 25,000 POUND CAPACITY AND THE REMAINING EIGHT TIEDOWN ANCHORS HAVE A 10,000 POUND CAPACITY. ALL ELEVEN TIEDOWN ANCHORS WILL ACCEPT 2" STEEL STRAPPING. SEE THE STRAPPING DETAIL ON PAGE 56. NOTE THAT THE STAKE POCKETS ON THE M1077 FLATRACK MAY ALSO BE USED FOR 2" STEEL HOLD-DOWN STRAPPING. SEE THE STRAPPING DETAIL ON PAGE 57.
5. WHEN LOADING THE M1077 FLATRACK, POSITION LOADS TIGHT AGAINST THE A-FRAME AT THE FORWARD END. LOADS OF 155MM AND/OR 8-INCH SEPARATE LOADING PROJECTILES MUST BE DIVIDED INTO SECTIONS WHICH MUST NOT EXCEED 11,000 POUNDS EACH. SEE THE LOADS ON PAGES 22 AND 28 FOR GUIDANCE. LOADS OF PALLETIZED UNITS, OTHER THAN SEPARATE LOADING PROJECTILES, HAVING A TOTAL WEIGHT OF 16,500 POUNDS OR MORE, MUST BE DIVIDED INTO TWO SECTIONS. SEE THE LOAD ON PAGE 24 FOR GUIDANCE.
6. WHEN LOADING THE M1 FLATRACK, POSITION THE LOAD TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER. SEE THE LOADS ON PAGES 4 THROUGH 21 FOR GUIDANCE.
7. TO ASSURE A TIGHT LOAD, ALL PALLET UNITS AND/OR OTHER ITEMS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY AS LOADING PROGRESSES.
8. PRIOR TO LOADING THE FLATRACK, DETERMINE THE QUANTITY OF PALLETIZED/SKIDDED UNIT(S) TO BE LOADED, SELECT THE BEST METHOD OF SECURING THE UNIT(S) FROM THE METHODS SHOWN WITHIN THIS DRAWING. NOTE: A COMBINATION OF THE METHODS SHOWN WITHIN THIS DRAWING MAY BE USED ON THE SAME FLATRACK.
9. THIS PROCEDURAL DRAWING INCLUDES PROCEDURES FOR BOTH PALLETIZED UNITS AND SKIDDED UNITS. THE GUIDANCE SHOWN FOR ONE TYPE OF UNIT MAY ALSO BE USED FOR THE OTHER TYPE OF UNIT.
10. TWO SETS OF FORKLIFT POCKETS ARE PROVIDED UNDERNEATH THE M1077 AND M1 FLATRACKS. THE SET NEAR THE ENDS OF THE FLATRACK MUST BE USED WHEN LIFTING LOADED FLATRACKS. THE SET CLOSEST TO THE CENTER OF THE FLATRACK IS FOR LIFTING UNLOADED FLATRACKS ONLY. USE OF THE WRONG FORKLIFT POCKETS COULD CAUSE DAMAGE TO EQUIPMENT. THE FORKS ON THE FORKLIFT MUST BE AT LEAST 70.00" LONG.

INDEX

ITEM	PAGE(S)
GENERAL NOTES AND MATERIAL SPECIFICATIONS - - - - -	2
LOADING PROCEDURES AND ITEMIZED INDEX - - - - -	3
<u>LOAD ON M1 FLATRACK</u>	
8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY - - - - -	4,5
155MM COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY - - - - -	6,7
120MM ARMOR COMBAT CONFIGURED LOAD - - - - -	8,9
COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY - - - - -	10,11
SMALL ARMS COMBAT CONFIGURED LOAD FOR INFANTRY - - - - -	12,13
MSB43 LINEAR DEMOLITION CHARGE (MICLIC)	
COMBAT CONFIGURED LOAD FOR ENGINEERS - - - - -	14,15
155MM SEPARATE LOADING PROJECTILES - - - - -	16,17
155MM PROPELLING CHARGE CONTAINERS - - - - -	18,19
MIXED BOX AMMUNITION - - - - -	20,21
<u>LOADS ON M1077 FLATRACK</u>	
8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY - - - - -	22,23
120MM ARMOR COMBAT CONFIGURED LOAD - - - - -	24,25
COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY - - - - -	26,27
155MM SEPARATE LOADING PROJECTILES - - - - -	28,29
155MM PROPELLING CHARGE CONTAINERS - - - - -	30,31
8-INCH SLP AND PROPELLING CHARGE CONTAINERS - - - - -	32,33
MSB43 LINEAR DEMOLITION CHARGE (MICLIC) - - - - -	34,35
DETAILS - - - - -	36-58



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY A (1 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 36.
- ② CENTER GATE ASSEMBLY B (1 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 36.
- ③ STRUT, 2" X 6" BY CUT-FOR-WEDGE-FIT (DOUBLED) (8 REQD). NAIL THE FIRST PIECE TO PIECES MARKED ① AND ② W/2-12d NAILS AT EACH END. NAIL THE SECOND PIECE TO THE FIRST PIECE W/3-10d NAILS AND TOENAIL TO PIECES MARKED ① AND ② W/2-12d NAILS AT EACH END. SEE GENERAL NOTE "N" ON PAGE 2.
- ④ HOLD-DOWN, 2" X 4" BY LENGTH-TO-SUIT (1 REQD). POSITION ON JOINTS BETWEEN PALLETS AT LOCATION SHOWN.
- ⑤ HOLD-DOWN ASSEMBLY B (2 REQD). POSITION ON TOP OF THE SEPARATE LOADING PROJECTILE PALLETS AS SHOWN. SEE DETAIL ON PAGE 46.
- ⑥ STRAPPING BOARD ASSEMBLY A (8 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO PIECE MARKED ④ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑦ HOLD-DOWN ASSEMBLY A (2 REQD). POSITION ON TOP OF THE PROPELLING CHARGE PALLETS AS SHOWN. SEE DETAIL ON PAGE 46.
- ⑧ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑭. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(KEY NUMBERS CONTINUED ON PAGE 5)

8-INCH COMBAT CONFIGURED LOAD				
DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D662	PROP CHG. 8-INCH 52.50 L X 40.75 W X 48.50 H	80	4 PALLETS	6,952 LBS
D624	PROJ. 8-INCH, M650 19.37 L X 28.50 W X 45.62 H	72	12 PALLETS	15,036 LBS
N340	FUZE, M739 14.63 L X 12.81 W X 8.56 H	32	2 BOXES	92 LBS
N463	FUZE, M728 14.63 L X 12.75 W X 12.00 H	48	3 BOXES	142 LBS
N523	PRIMER, M82 24.13 L X 12.00 W X 11.25 H	500	1 BOX	37 LBS

8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY

SPECIAL NOTES:

1. A TYPICAL 8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE 8-INCH COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 4 IS SHOWN AS TYPICAL. IF LOADING PALLETES OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETES ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETES TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. WHEN POSITIONING LOOSE BOXES ON TOP OF A LOAD, POSITION THE BOXES BETWEEN TWO STRAPPING BOARD ASSEMBLIES WHEN POSSIBLE. THIS WILL HELP PROVIDE LONGITUDINAL SUPPORT ALONG WITH THE LOOSE BOX HOLD-DOWN STRAPS.
7. FOR THE SAME COMBAT CONFIGURED LOAD ON THE M1077 FLATRACK, SEE PAGES 22 AND 23.


(KEY NUMBERS CONTINUED FROM PAGE 4)

- ⑨ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (3 REQD). INSTALL EACH STRAP TO ENCIRCLE ALL FOUR Laterally ADJACENT PALLET UNITS, UNDER THE SKID BASE AND OVER TOP OF COVER. POSITION STRAPS AT CENTER OF PALLETES. SEAL EACH STRAP WITH ONE SEAL MARKED ⑨. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑩ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D662 PROPELLING CHARGE PALLET (THREAD STRAPS UNDER TOP DECK OF PALLET BASE) AND THE TWO LOOSE N340 FUZE BOXES AS SHOWN. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑪ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D662 PROPELLING CHARGE PALLET (THREAD STRAPS UNDER TOP DECK OF PALLET BASE) AND THE LOOSE N523 BOX OF PRIMERS AS SHOWN. SEAL EACH STRAP WITH ONE SEAL MARKED ⑪. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑫ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D662 PROPELLING CHARGE PALLET (THREAD STRAPS UNDER TOP DECK OF PALLET BASE) AND THE TWO LOOSE N463 FUZE BOXES AS SHOWN. SEAL EACH STRAP WITH ONE SEAL MARKED ⑫. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑬ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D662 PROPELLING CHARGE PALLET (THREAD STRAPS UNDER TOP DECK OF PALLET BASE) AND THE LOOSE N463 FUZE BOX AS SHOWN. SEAL EACH STRAP WITH ONE SEAL MARKED ⑬. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑭ SEAL FOR 2" STEEL STRAPPING (32 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑭. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑮ SEAL FOR 1-1/4" STEEL STRAPPING (3 REQD). ONE SEAL FOR EACH STRAP MARKED ⑮. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑯ SEAL FOR 3/4" STEEL STRAPPING (8 REQD). ONE SEAL FOR EACH STRAP MARKED ⑯, ⑰, ⑱ AND ⑲. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 2"	20	7
2" X 4"	141	94
2" X 6"	135	135
NAILS	NO. REQD	POUNDS
10d (3")	227	3-1/2
12d (3-1/4")	32	1/2
STEEL STRAPPING, 2"	164' REQD	55 LBS
STEEL STRAPPING, 1-1/4"	68' REQD	10 LBS
STEEL STRAPPING, 3/4"	150' REQD	11 LBS
SEAL FOR 2" STRAPPING	32 REQD	7 LBS
SEAL FOR 1-1/4" STRAPPING	3 REQD	NIL
SEAL FOR 3/4" STRAPPING	8 REQD	NIL

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
8-INCH CCL	1	22,259 LBS
DUNNAGE		559 LBS
TOTAL WEIGHT		22,818 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY C (1 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 37.
- ② SPACER ASSEMBLY A (2 REQD). POSITION BETWEEN THE D544 SLP PALLETS AT LOCATIONS SHOWN. SEE DETAIL ON PAGE 48.
- ③ HOLD-DOWN ASSEMBLY B (4 REQD). POSITION ON TOP OF THE SEPARATE LOADING PROJECTILE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ④ HOLD-DOWN, 2" X 4" X 58" (4 REQD). POSITION ON EDGE OF SLP PALLETS AT LOCATIONS SHOWN.
- ⑤ STRAPPING BOARD ASSEMBLY A (5 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ④ W/2-10d NAILS AT EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑥ FILL PIECE, 1" X 4" X 27" (4 REQD). POSITION TWO AT EACH END OF NINE BUNDLED BOXES OF M762 (N289) FUZES. SEE THE DETAIL ON PAGE 7.
- ⑦ FILLER ASSEMBLY A (1 REQD). POSITION ON TOP OF THE NINE BUNDLED BOXES OF M762 (N289) FUZES. SEE DETAIL ON PAGE 46.
- ⑧ STRAPPING BOARD ASSEMBLY C (2 REQD). POSITION ON TOP OF THE D533 PROPELLING CHARGE PALLETS AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑨ STRAPPING BOARD ASSEMBLY E (2 REQD). POSITION ON TOP OF THE D541 PROPELLING CHARGE PALLETS AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑩ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (9 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE "HOLD-DOWN STRAP THREADING" DETAIL ON PAGE 56.

(CONTINUED ON PAGE 7)


155MM COMBAT CONFIGURED LOAD

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D544	PROJ, 155MM, M107/M795 HE 13.63 L X 27.13 W X 31.25 H	32	4 PALLETS	3,188 LBS
D563	PROJ, 155MM, M483A1 DPICM 14.62 L X 29.12 W X 39.38 H	144	18 PALLETS	15,732 LBS
D541	PROP CHG, M4 55.00 L X 40.00 W X 44.88 H	168	2 PALLETS	3,532 LBS
D533	PROP CHG, M119A2 47.50 L X 35.75 W X 49.00 H	60	2 PALLETS	3,124 LBS
N340	FUZE, M739 14.87 L X 13.00 W X 9.25 H	16	1 BOX	56 LBS
N463	FUZE, M728 14.63 L X 12.75 W X 12.00 H	16	1 BOX	48 LBS
N289	FUZE, M762, 14.63 L X 12.87 W X 9.12 H	144	9 BOXES	377 LBS
N523	PRIMER, M82 24.13 L X 12.00 W X 11.25 H	500	1 BOX	62 LBS

155MM COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY

SPECIAL NOTES:

1. A TYPICAL 155MM COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE 155MM COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 6 IS SHOWN AS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. WHEN POSITIONING LOOSE BOXES ON TOP OF A LOAD, POSITION THE BOXES BETWEEN TWO STRAPPING BOARD ASSEMBLIES WHEN POSSIBLE. THIS WILL HELP PROVIDE LONGITUDINAL SUPPORT ALONG WITH THE LOOSE BOX HOLD-DOWN STRAPS.
7. THE METHOD SHOWN FOR STRAPPING LOOSE BOXES ON TOP OF PALLET UNITS IS AN ALTERNATIVE METHOD. IF DESIRED BOTH STRAPS MAY BE POSITIONED IN A LONGITUDINAL DIRECTION AS SHOWN IN THE LOAD ON PAGE 4.




BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 4"	20	7
2" X 2"	9	3
2" X 4"	188	126
2" X 6"	44	44
NAILS	NO. REQD	POUNDS
10d (3")	224	3-1/2
STEEL STRAPPING, 2" - - - - 188' REQD - - - - 66 LBS		
STEEL STRAPPING, 1-1/4" - - 96' REQD - - - - 14 LBS		
STEEL STRAPPING, 3/4" - - - 142' REQD - - - - 11 LBS		
SEAL FOR 2" STRAPPING - - - - 36 REQD - - - - 8 LBS		
SEAL FOR 1-1/4" STRAPPING - - 4 REQD - - - - NIL		
SEAL FOR 3/4" STRAPPING - - - 8 REQD - - - - NIL		

(KEY NUMBERS CONTINUED FROM PAGE 6)

- ⑪ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (4 REQD). INSTALL EACH STRAP TO ENCIRCLE ALL Laterally ADJACENT PALLET UNITS UNDER THE SKID BASE AND OVER TOP OF COVER. POSITION STRAPS AT CENTER OF PALLETS. SEAL WITH ONE SEAL MARKED ⑦. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑫ BUNDLING STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE NINE BOXES OF M762 (N289) FUZES AND FILL PIECES MARKED ⑥. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑬ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D533 PROPELLING CHARGE PALLET (THREAD STRAP UNDER TOP DECK OF PALLET BASE) AND THE LOOSE N523 BOX OF PRIMERS AS SHOWN. ONE STRAP ENCIRCLES PALLET AND PRIMER BOX Laterally AND ONE STRAP ENCIRCLES PALLET AND PRIMER BOX LONGITUDINALLY. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. NOTE THAT THESE STRAPS MUST BE PREPOSITIONED PRIOR TO POSITIONING PALLET. SEE SPECIAL NOTE 7 ON THIS PAGE AND GENERAL NOTE "M" ON PAGE 2.
- ⑭ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D541 PROPELLING CHARGE PALLET (THREAD STRAP UNDER TOP OF DECK OF PALLET BASE) AND THE N340 FUZE BOX AS SHOWN. ONE STRAP ENCIRCLES PALLET AND FUZE BOX Laterally AND ONE STRAP ENCIRCLES PALLET AND FUZE BOX LONGITUDINALLY. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE SPECIAL NOTE 7 ON THIS PAGE AND GENERAL NOTE "M" ON PAGE 2.
- ⑮ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE D541 PROPELLING CHARGE PALLET (THREAD STRAP UNDER TOP OF DECK OF PALLET BASE) AND THE N463 FUZE BOX AS SHOWN. ONE STRAP ENCIRCLES PALLET AND FUZE BOX Laterally AND ONE STRAP ENCIRCLES THE PALLET AND FUZE BOX LONGITUDINALLY. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE SPECIAL NOTE 7 ON THIS PAGE AND GENERAL NOTE "M" ON PAGE 2.
- ⑯ SEAL FOR 2" STEEL STRAPPING (36 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑩. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑰ SEAL FOR 1-1/4" STEEL STRAPPING (4 REQD). DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑱ SEAL FOR 3/4" STEEL STRAPPING (8 REQD). ONE SEAL FOR EACH STRAP MARKED ⑩, ⑬, ⑭ AND ⑮. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
155MM CCL - - - - -	1 - - - - -	25,779 LBS
DUNNAGE - - - - -	- - - - -	463 LBS
TOTAL WEIGHT - - - - -		26,242 LBS



INDICATES 2
C787 120MM
AMMO PALLETS.

AFT END.

ISOMETRIC VIEW

INDICATES 8
C786 120MM
AMMO PALLETS.

INDICATES
TIEDOWN ANCHOR.

KEY NUMBERS

- ① CENTER GATE ASSEMBLY D (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 37.
- ② STRUT, 2" X 6" BY CUT-FOR-WEDGE-FIT (DOUBLED) (8 REQD). NAIL THE FIRST PIECE TO PIECE MARKED ① W/2-12d NAILS AT EACH END. NAIL THE SECOND PIECE TO THE FIRST PIECE W/3-10d NAILS AND TOENAIL TO PIECE MARKED ① W/2-12d NAILS AT EACH END. SEE GENERAL NOTE "N" ON PAGE 2.
- ③ HOLD-DOWN ASSEMBLY A (4 REQD). POSITION ON TOP OF THE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ④ HOLD-DOWN, 2" X 4" BY LENGTH-TO-SUIT (2 REQD). POSITION ON JOINTS BETWEEN PALLETS AT LOCATIONS SHOWN.
- ⑤ STRAPPING BOARD ASSEMBLY A (9 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ④ W/2-10d NAILS AT EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑥ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (9 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑦. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑦ SEAL FOR 2" STEEL STRAPPING (36 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑥. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

120MM COMPLETE ROUND CONFIGURED LOAD

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
C786	CTG, 120MM M829 39.50 L X 44.50 W X 51.50 H	240	8 PALLETS	19,128 LBS
C787	CTG, 120MM M830 40.13 L X 44.50 W X 51.75 H	60	2 PALLETS	4,866 LBS

120MM ARMOR COMBAT CONFIGURED LOAD


SPECIAL NOTES:

1. A TYPICAL 120MM ARMOR COMBAT CONFIGURED LOAD IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE 120MM COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 8 IS SHOWN AS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE 120MM PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. FOR THE SAME COMBAT CONFIGURED LOAD ON THE M1077 FLATRACK, SEE PAGES 24 AND 25.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 4"	166	111
2" X 6"	130	130
NAILS	NO. REQD	POUNDS
10d (3")	223	3-1/4
12d (3-1/4")	64	1-1/4
STEEL STRAPPING, 2" - - - - 196' REQD - - - - 66 LBS		
SEAL FOR 2" STRAPPING - - - - 36 REQD - - - - 8 LBS		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
120MM CCL - - - - -	1 - - - - -	23,994 LBS
DUNNAGE - - - - -	- - - - -	561 LBS
TOTAL WEIGHT - - - - -		24,555 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY E (1 REQD). POSITION AT THE LOCATION SHOWN. SEE THE DETAIL ON PAGE 38.
- ② HOLD-DOWN ASSEMBLY A (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 46.
- ③ HOLD-DOWN, 2" X 4" BY LENGTH-TO SUIT (1 REQD). POSITION ON CENTER JOINT BETWEEN LATERALLY ADJACENT PALLETS.
- ④ STRAPPING BOARD ASSEMBLY A (4 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLDDOWN PIECES MARKED ③ W/2-10d NAILS AT EACH END. SEE THE DETAIL ON PAGE 44.
- ⑤ STRAPPING BOARD ASSEMBLY D (2 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑥ STRAPPING BOARD ASSEMBLY C (2 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑦ SOLID FILL, 2" X 6" X 42-1/2" (DOUBLED) (2 REQD). CENTER ON THE VERTICAL PIECES ON THE CENTER GATE ASSEMBLY AND NAIL FIRST PIECE TO THE LOAD BEARING PIECES ON THE CENTER GATE W/3-10d NAILS AT EACH JOINT. NAIL SECOND PIECE TO THE FIRST PIECE W/7-10d NAILS.
- ⑧ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑨. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑨ SEAL FOR 2" STEEL STRAPPING (32 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑧. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY				
DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
PL94	STINGER RMP, FIM 92C 39.37 L X 67.25 W X 36.50 H	36	4 PALLETS	2,996 LBS
P893	TOW IIA BGM-71D 48.00 L X 58.25 W X 39.75 H	12	1 PALLET	1,127 LBS
A974	25MM CARTRIDGE, APOS-T, M791 31.50 L X 45.00 W X 42.50 H	600	1 PALLET	1,241 LBS
A975	25MM CARTRIDGE, HEI-T, M792 31.50 L X 45.00 W X 42.50 H	1,200	2 PALLETS	2,482 LBS


SPECIAL NOTES:

1. A TYPICAL COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 10 IS SHOWN AS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. FOR THE SAME COMBAT CONFIGURED LOAD ON THE M1077 FLATRACK, SEE PAGES 26 AND 27.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 4"	145	97
2" X 6"	81	81
NAILS	NO. REQD	POUNDS
10d (3")	206	3-1/4
STEEL STRAPPING, 2" - - - - 164' REQD - - - - 55 LBS		
SEAL FOR 2" STRAPPING - - - - 32 REQD - - - - 5 LBS		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
CCL - - - - -	1 - - - - -	7,846 LBS
DUNNAGE - - - - -	- - - - -	420 LBS
TOTAL WEIGHT - - - - -		8,266 LBS



(KEY NUMBERS CONTINUED)

- ⑧ SEAL FOR 2" STEEL STRAPPING (32 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑧. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑨ SEAL FOR 1-1/4" STEEL STRAPPING (2 REQD). ONE SEAL FOR EACH STRAP MARKED ⑨. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑩ SEAL FOR 3/4" STEEL STRAPPING (3 REQD). ONE SEAL FOR EACH STRAP MARKED ⑩. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.

KEY NUMBERS

- ① SPACER ASSEMBLY B (1 REQD). POSITION BETWEEN THE 5.56MM PALLET AND THE PALLET OF HAND GRENADES. SEE THE DETAIL ON PAGE 48.
- ② CENTER GATE ASSEMBLY F (2 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 38.
- ③ STRUT, 2" X 6" BY CUT-FOR-WEDGE-FIT (DOUBLED) (15 REQD). NAIL THE FIRST PIECE TO PIECES MARKED ② W/2-12d NAILS AT EACH END. NAIL THE SECOND PIECE TO THE FIRST PIECE W/3-10d NAILS AND TOENAIL TO PIECE MARKED ② W/2-12d NAILS AT EACH END. SEE GENERAL NOTE "N" ON PAGE 2.
- ④ STRAPPING BOARD ASSEMBLY C (8 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑤ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (3 REQD). INSTALL EACH STRAP TO ENCIRCLE THE G881 GRENADE PALLET (THREAD STRAPS UNDER TOP DECK OF PALLET BASE) AND THE TWO LOOSE A363 9MM BOXES AS SHOWN. ONE STRAP ENCIRCLES PALLET AND BOTH 9MM BOXES LATERALLY AND TWO STRAPS ENCIRCLE THE PALLET AND 9MM BOXES LONGITUDINALLY. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. NOTE THAT THESE STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLET. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑥ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE ALL FOUR .50 CAL A576 PALLETS AT LOCATIONS SHOWN. SEAL EACH STRAP WITH ONE SEAL MARKED ⑩. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑦ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(CONTINUED AT LEFT)

SMALL ARMS COMBAT CONFIGURED LOAD

DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
A131	7.62MM CARTRIDGE 46.00 L X 35.00 W X 46.12 H	64,000	2 PALLETS	6,362 LBS
A068	5.56MM CARTRIDGE 51.00 L X 43.50 W X 39.00 H	78,720	1 PALLET	3,016 LBS
A071	5.56MM CARTRIDGE 51.00 L X 43.50 W X 39.00 H	80,640	1 PALLET	3,388 LBS
A576	.50 CAL CARTRIDGE 51.00 L X 43.50 W X 22.25 H	19,200	4 PALLETS	7,736 LBS
G881	HAND GRENADE 45.75 L X 37.87 W X 39.25 H	720	1 PALLET	1,309 LBS
K143	MINE, ANTIPERSONNEL 53.50 L X 42.25 W X 35.75 H	192	1 PALLET	1,808 LBS
A363	9MM CARTRIDGE 14.43 L X 12.53 W X 8.12 H	4,000	2 BOXES	160 LBS

SMALL ARMS AMMO COMBAT CONFIGURED LOAD FOR INFANTRY


SPECIAL NOTES:

1. A TYPICAL SMALL ARMS COMBAT CONFIGURED LOAD FOR INFANTRY IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE SMALL ARMS AMMO COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 12 IS SHOWN AS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHT, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. WHEN POSITIONING LOOSE BOXES ON TOP OF A LOAD, CENTER THE BOXES BETWEEN TWO STRAPPING BOARD ASSEMBLIES AS SHOWN. THIS WILL HELP PROVIDE LONGITUDINAL SUPPORT ALONG WITH THE LOOSE HOLD-DOWN STRAPS.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 2"	12	4
2" X 4"	118	73
2" X 6"	147	147
NAILS	NO. REQD	POUNDS
10d (3")	316	5
12d (3-1/4")	120	2
STEEL STRAPPING, 2" - - - - 164' REQD - - - - 55 LBS		
STEEL STRAPPING, 1-1/4" - - 49' REQD - - - - 7 LBS		
STEEL STRAPPING, 3/4" - - - 48' REQD - - - - 4 LBS		
SEAL FOR 2" STRAPPING - - - - 32 REQD - - - - 7 LBS		
SEAL FOR 1-1/4" STRAPPING - - 2 REQD - - - - NIL		
SEAL FOR 3/4" STRAPPING - - - 3 REQD - - - - NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
SMALL ARMS CCL - - - - - 1 - - - - -		23,779 LBS
DUNNAGE - - - - -		528 LBS
TOTAL WEIGHT - - - - -		24,307 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY H (1 REQD). POSITION BETWEEN DEMO CHARGE CONTAINERS. SEE THE DETAIL ON PAGE 39.
- ② CENTER GATE ASSEMBLY G (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 39.
- ③ STRUT, 4" X 4" BY CUT-FOR-WEDGE-FIT (4 REQD). TOENAIL TO THE LOAD BEARING PIECES OF CENTER GATE ASSEMBLY G W/2-16d NAILS AT EACH END.
- ④ STRAPPING BOARD ASSEMBLY C (6 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑤ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (6 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑧. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑥ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF DEMO CONTAINER AND SEAL WITH TWO SEALS PIECES MARKED ⑧. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑦ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (16 REQD). POSITION UNDER STRAPS MARKED ⑤ AND ⑥ AT EDGE OF DEMO CONTAINERS.
- ⑧ SEAL FOR 2" STEEL STRAPPING (32 REQD) FOUR SEALS FOR EACH STRAP MARKED ⑤ AND ⑥. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

M58A3 LINEAR DEMOLITION CHARGE (MICLIC) CCL

DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
M913	DEMO CHARGE M58A3 83.25 L X 53.75 W X 24.75 H	4	4 CNTRS	11,600 LBS
J143	5-INCH ROCKET MOTOR 92.50 L X 22.50 W X 13.50 H	4	4 BOXES	800 LBS


SPECIAL NOTES:

1. A TYPICAL MICLIC DEMOLITION CHARGE COMBAT CONFIGURED LOAD FOR ENGINEERS IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE MICLIC M58A3 DEMOLITION CHARGE IN METAL CONTAINERS AND THE ROCKET MOTOR IN WOODEN BOXES IN THE LOAD ON PAGE 14 ARE SHOWN AS TYPICAL. IF LOADING SIMILAR TYPE CONTAINERS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE CONTAINERS, ASSURE THAT ALL STEEL STRAPPING ON EACH CONTAINER IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE DEMOLITION CHARGE CONTAINERS AND ROCKET MOTOR BOXES TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL CONTAINERS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 2"	15	5
2" X 4"	43	29
2" X 6"	75	75
4" X 4"	10	14
NAILS	NO. REQD	POUNDS
10d (3")	204	3-1/4
16d (3-1/2")	16	1/2
STEEL STRAPPING, 2"	164' REQD	55 LBS
SEAL FOR 2" STRAPPING	32 REQD	-7 LBS
EDGE PROTECTORS	AS REQD	NIL

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
DEMO CHARGE M58A3	4	11,600 LBS
5-INCH ROCKET MOTOR	4	800 LBS
DUNNAGE		312 LBS
TOTAL WEIGHT		12,712 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY J (2 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 40.
- ② STRUT, 2" X 6" BY CUT-FOR-WEDGE-FIT (DOUBLED) (8 REQD). NAIL THE FIRST PIECE TO PIECE MARKED ① W/2-12d NAILS EACH END. NAIL THE SECOND PIECE TO THE FIRST W/4-10d NAILS AND TOENAIL TO PIECE MARKED ① W/2-12d NAILS EACH END. SEE GENERAL NOTE "N" ON PAGE 2.
- ③ HOLD-DOWN ASSEMBLY B (6 REQD). POSITION ON TOP OF THE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ④ HOLD-DOWN, 2" X 4" BY LENGTH-TO-SUIT (6 REQD). POSITION ON JOINTS BETWEEN PALLETS AT LOCATIONS SHOWN.
- ⑤ STRAPPING BOARD ASSEMBLY A (9 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ④ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑥ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (6 REQD). INSTALL EACH STRAP TO ENCIRCLE ALL LATERALLY ADJACENT PALLET UNITS UNDER THE SKID BASE AND OVER TOP OF COVER. POSITION STRAPS AT CENTER OF PALLETS. SEAL EACH STRAP WITH ONE SEAL MARKED ⑧. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑦ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (9 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS PIECES MARKED ⑧. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2, AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑧ SEAL FOR 1-1/4" STEEL STRAPPING (6 REQD) ONE SEAL FOR EACH STRAP MARKED ⑥, DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑨ SEAL FOR 2" STEEL STRAPPING (36 REQD) FOUR SEALS FOR EACH STRAP MARKED ⑦, DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

TYPICAL AMMUNITION ITEM

DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D563	PROJ, 155MM, 483A1 DPICM 14.62 L X 29.12 W X 39.38 H	256	32 PALLETS	27,968 LBS

155MM SEPARATE LOADING PROJECTILES


SPECIAL NOTES:

1. A TYPICAL LOAD OF 32 PALLETS OF 155MM SEPARATE LOADING PROJECTILES IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE 155MM SLP PALLET HAVING DIMENSIONS OF 29-1/8" WIDE BY 14-5/8" LONG BY 39-3/8" HIGH AND WEIGHING 874 POUNDS IS SHOWN AS TYPICAL. IF LOADING SLP PALLETS OF OTHER QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE SLP PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally and Longitudinally TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. FOR THE SAME ITEM ON THE M1077 FLATRACK, SEE PAGES 28 AND 29.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 2"	13	5
2" X 4"	176	118
2" X 6"	100	100
NAILS	NO. REQD	POUNDS
10d (3")	205	3-1/4
12d (3-1/4")	32	3/4
STEEL STRAPPING, 1-1/4" - - - 138' REQD - - - 20 LBS		
STEEL STRAPPING, 2" - - - 216' REQD - - - 72 LBS		
SEAL FOR 1-1/4" STRAPPING - - 6 REQD - - - 1/4 LB		
SEAL FOR 2" STRAPPING - - - 36 REQD - - 7-1/2 LBS		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
155MM SLP PALLET - - - - 32	- - - - -	27,968 LBS
DUNNAGE - - - - -	- - - - -	550 LBS
TOTAL WEIGHT - - - - -		28,518 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY K (1 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 40.
- ② STRAPPING BOARD ASSEMBLY E (8 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ③ HOLD-DOWN STRAP, 2" X .044" OR .50" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ④. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ④ SEAL FOR 2" STEEL STRAPPING (32 REQD). FOUR SEALS FOR EACH STRAP MARKED ③, DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

TYPICAL AMMUNITION ITEMS

DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D541	PROP CHARGE, 155MM M4 55.00 L X 40.00 W X 44.88 H	400	8 PALLETS	14,128 LBS

155MM PROPELLING CHARGE CONTAINERS


SPECIAL NOTES:

1. A TYPICAL LOAD OF 8 PALLETS OF 155MM PROPELLING CHARGE CONTAINERS IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE D541 155MM PROPELLING CHARGE PALLET, 50 CONTAINERS PER PALLET, HAVING DIMENSIONS OF 55" LONG BY 40" WIDE BY 44-7/8" HIGH AND WEIGHING 1,766 POUNDS IS SHOWN AS TYPICAL. IF LOADING PALLETIZED UNITS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.
6. FOR THE SAME ITEM ON THE M1077 FLATRACK SEE PAGES 30 AND 31.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 4"	74	50
2" X 6"	34	34
NAILS	NO. REQD	POUNDS
10d (3")	80	1-1/4
STEEL STRAPPING, 2" - - - - 216' REQD - - - - 72 LBS		
SEAL FOR 2" STRAPPING - - - - 36 REQD - - 7-1/2 LBS		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
155MM PC		
PALLET - - - - -	8 - - - - -	14,128 LBS
DUNNAGE - - - - -	- - - - -	250 LBS
TOTAL WEIGHT - - - - -		14,378 LBS



ISOMETRIC VIEW

KEY NUMBERS

- ① CENTER GATE ASSEMBLY L (2 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 41.
- ② STRUT, 2" X 6" BY CUT-FOR-WEDGE-FIT (DOUBLED) (12 REQD). NAIL THE FIRST PIECE TO PIECE MARKED ① W/2-12d NAILS AT EACH END. NAIL SECOND PIECE TO FIRST PIECE W/4-10d NAILS AND TOENAIL TO PIECE MARKED ① W/2-12d NAILS EACH END. SEE GENERAL NOTE "N" ON PAGE 2.
- ③ SOLID FILL, SIX INCH WIDE MATERIAL BY THICKNESS REQUIRED TO FILL VOID SPACE BETWEEN GATE MARKED ① AND THE 66MM LAW RKT PALLET, BY 33" LONG (REF: 2" X 6" X 33") (3 REQD). NAIL TO THE LOAD BEARING PIECES ON GATE MARKED ① W/5-10d NAILS EACH PIECE.
- ④ SOLID FILL, SIX INCH WIDE MATERIAL BY THICKNESS REQUIRED TO FILL VOID SPACE BETWEEN GATE MARKED ① AND THE 5.56MM CTG PALLET, (REF: 2" X 6" X 51" AND 1" X 6" X 51") (3 REQD). NAIL FIRST PIECE TO THE LOAD BEARING PIECES ON PIECE MARKED ① W/5-10d NAILS. NAIL SECOND PIECE TO FIRST PIECE IN A LIKE MANNER.
- ⑤ FILLER ASSEMBLY B (1 REQD). POSITION ON TOP OF THE 25MM CARTRIDGE PALLET. SEE THE DETAIL ON PAGE 47.
- ⑥ STRAPPING BOARD ASSEMBLY C (6 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑦ STRAPPING BOARD ASSEMBLY F (2 REQD). POSITION ON TOP OF THE 7.62MM CARTRIDGE PALLET AND THE HAND GRENADE PALLET AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑧ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑨. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑨ SEAL FOR 2" STEEL STRAPPING (32 REQD) FOUR SEALS FOR EACH STRAP MARKED ⑧. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

TYPICAL AMMUNITION ITEMS

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
C869	81MM CARTRIDGE 51.00 L X 42.00 W X 44.87 H	180	2 PALLETS	3,596 LBS
A072	5.56MM CARTRIDGE 51.00 L X 43.50 W X 39.00 H	80,640	1 PALLET	3,401 LBS
C995	84MM AT4 ROCKET 45.87 L X 35.50 W X 39.00 H	20	1 PALLET	529 LBS
A976	25MM CARTRIDGE, M621 CNTR 53.00 L X 43.00 W X 21.37 H	810	1 PALLET	1,515 LBS
H557	66MM LAW ROCKET 41.25 L X 33.50 W X 36.87 H	45	1 PALLET	398 LBS
A131	7.62MM CARTRIDGE 46.00 L X 35.00 W X 46.12 H	32,000	1 PALLET	3,181 LBS
G881	HAND GRENADE 45.75 L X 37.87 W X 39.25 H	720	1 PALLET	1,309 LBS

MIXED BOXED AMMUNITION


SPECIAL NOTES:

1. A TYPICAL LOAD OF MIXED BOXED AMMUNITION IS SHOWN LOADED ON THE M1 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 18'-6" LONG AND A MAXIMUM LOAD WEIGHT OF 28,750 POUNDS.
2. THE MIXED BOXED AMMUNITION SHOWN IN THE CHART ON PAGE 20 IS SHOWN AS TYPICAL. IF LOADING PALLETIZED UNITS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE PALLETS TIGHT AGAINST THE FORWARD END WALL AND THE AFT END WALL, LEAVING THE EXCESS SPACE IN THE CENTER AS SHOWN. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STEEL STRAPPING IS IN POSITION.
5. THE EXCESS SPACE REMAINING AFTER THE LOAD IS IN POSITION MUST BE FILLED WITH CENTER GATES AND STRUTS OR OTHER TYPES OF BLOCKING ASSEMBLIES AS REQUIRED TO ASSURE A LONGITUDINALLY TIGHT LOAD.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 4"	4	2
1" X 6"	13	7
2" X 2"	44	15
2" X 4"	81	54
2" X 6"	268	268
NAILS	NO. REQD	POUNDS
10d (3")	560	8-1/2
12d (3-1/4")	96	1-1/2
STEEL STRAPPING, 2" - - - - 164' REQD - - - - 55 LBS		
SEAL FOR 2" STRAPPING - - - - 32 REQD - - - - -7 LBS		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
BOXED AMMO PALLETS	-- 8	13,929 LBS
DUNNAGE	- - - - -	764 LBS
TOTAL WEIGHT		- - - - - 14,693 LBS



KEY NUMBERS

- ① END GATE ASSEMBLY A (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 49.
- ② CENTER GATE ASSEMBLY N (1 REQD). POSITION BETWEEN 8-INCH SLP PALLETS AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 42.
- ③ CENTER GATE ASSEMBLY M (1 REQD). POSITION BETWEEN 8-INCH SLP PALLETS AND 8-INCH PROPELLING CHARGE PALLETS. SEE THE DETAIL ON PAGE 41.
- ④ END GATE ASSEMBLY B (1 REQD). POSITION AT THE AFT END OF THE LOAD. SEE THE DETAIL ON PAGE 49.
- ⑤ HOLD-DOWN, 2" X 4" BY LENGTH-TO-SUIT (2 REQD). POSITION ON JOINT BETWEEN 8-INCH SLP PALLETS.
- ⑥ HOLD-DOWN ASSEMBLY B (4 REQD). POSITION ON TOP OF THE 8-INCH SLP PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ⑦ HOLD-DOWN ASSEMBLY A (2 REQD). POSITION ON TOP OF PROP CHARGE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ⑧ STRAPPING BOARD ASSEMBLY A (8 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ⑤ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑨ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (3 REQD). INSTALL EACH STRAP TO ENCIRCLE ALL LATERALLY ADJACENT SLP PALLETS IN EACH ROW, UNDER THE SKID BASE AND OVER TOP OF COVER. SEAL WITH ONE SEAL MARKED ②. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑩ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE PROPELLING CHARGE PALLET AND THE LOOSE BOX OF N523 PRIMERS AS SHOWN. THREAD STRAPS UNDER TOP DECK OF PROPELLING CHARGE PALLET. SEAL EACH STRAP WITH ONE SEAL MARKED ②. NOTE: THESE TWO STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLETS. SEE GENERAL NOTE "M" ON PAGE 2.

(CONTINUED AT LEFT)

(KEY NUMBERS CONTINUED)

- ⑪ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (4 REQD). INSTALL EACH STRAP TO ENCIRCLE THE PROPELLING CHARGE PALLET AND THE LOOSE BOXES OF N463 PRIMERS AS SHOWN. THREAD STRAPS UNDER TOP DECK OF PROPELLING CHARGE PALLET. SEAL EACH STRAP WITH ONE SEAL MARKED ②. NOTE: THESE TWO STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLETS. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑫ LOOSE BOX HOLD-DOWN STRAP, 3/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE THE PROPELLING CHARGE PALLET AND THE LOOSE BOXES OF N340 PRIMERS AS SHOWN. THREAD STRAPS UNDER TOP DECK OF PROPELLING CHARGE PALLET. SEAL EACH STRAP WITH ONE SEAL MARKED ②. NOTE: THESE TWO STRAPS MUST BE PRE-POSITIONED PRIOR TO POSITIONING PALLETS. SEE GENERAL NOTE "M" ON PAGE 2.

(CONTINUED ON PAGE 23)

8-INCH COMBAT CONFIGURED LOAD

DODIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D662	PROP CHG. 8-INCH 52.50 L X 40.75 W X 48.50 H	80	4 PALLETS	6,952 LBS
D624	PROJ. 8-INCH M650 19.37 L X 28.50 W X 45.62 H	72	12 PALLETS	15,036 LBS
N340	FUZE, M739 14.63 L X 12.81 W X 8.50 H	32	2 BOXES	92 LBS
N463	FUZE, M728 14.63 L X 12.75 W X 12.00 H	48	3 BOXES	142 LBS
N523	PRIMER, M82 24.13 L X 12.00 W X 11.25 H	500	1 BOX	37 LBS

8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY

SPECIAL NOTES:

1. A TYPICAL 8-INCH COMBAT CONFIGURED LOAD FOR FIELD ARTILLERY IS SHOWN LOADED ON THE 16-1/2-TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE 8-INCH COMBAT CONFIGURED LOAD IN THE CHART ON PAGE 22 IS SHOWN AS TYPICAL. IF LOADING PALLETTS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETTS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. DUE TO WEIGHT, HIGH CENTER OF GRAVITY, AND SMALL SKID AREA CONTACTING THE STEEL FLOOR, SEPARATE LOADING PROJECTILE PALLETTS MUST BE DIVIDED INTO SECTIONS NOT EXCEEDING 11,000 POUNDS. EACH SECTION MUST BE SECURED WITH A GATE AND STEEL STRAPPING AS SHOWN IN THE LOAD ON PAGE 22. NOTE THAT THE 12 PALLETTS OF 8-INCH PROJECTILES SHOWN IN THE LOAD ON PAGE 22 HAVE A TOTAL WEIGHT OF 15,036 POUNDS. THE LOAD THEREFORE, WAS DIVIDED INTO TWO SECTIONS, WITH ONE SECTION WEIGHING 10,024 POUNDS AND ONE SECTION WEIGHING 5,012 POUNDS.
5. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER LATERALLY AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STRAPPING IS IN POSITION.
6. FOR EASE OF LOADING AND SECUREMENT OF THE LOAD, EACH ROW OF SEPARATE LOADING PROJECTILES POSITIONED ACROSS THE WIDTH OF THE FLATRACK MUST CONTAIN THE SAME QUANTITY. USE AN "OMITTED SLP PALLETIZED UNIT ASSEMBLY" FOR EACH OMITTED UNIT AS NECESSARY TO MAINTAIN EVEN ROWS. SEE THE "OMITTED SLP PALLET UNIT ASSEMBLY" DETAIL ON PAGE 58.
7. WHEN POSITIONING LOOSE BOXES ON TOP OF A LOAD, CENTER THE BOXES BETWEEN TWO STRAPPING BOARD ASSEMBLIES WHEN POSSIBLE. THIS WILL HELP PROVIDE LONGITUDINAL SUPPORT ALONG WITH THE LOOSE BOX HOLD-DOWN STRAPS.
8. FOR THIS SAME 8-INCH COMBAT CONFIGURED LOAD ON THE M1 FLATRACK SEE PAGES 4 AND 5.

(KEY NUMBERS CONTINUED)

- ⑫ SEAL FOR 3/4" STEEL STRAPPING (8 REQ'D). ONE SEAL FOR EACH STRAP MARKED ⑩, ⑪ AND ⑫. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑬ SEAL FOR 1-1/4" STEEL STRAPPING (3 REQ'D). ONE SEAL FOR EACH STRAP MARKED ⑬. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑭ SEAL FOR 2" STEEL STRAPPING (64 REQ'D). SIX SEALS FOR EACH STRAP THREADED THRU THE STAKE POCKETS AND FOUR SEALS FOR EACH STRAP ATTACHED TO TIEDOWN ANCHORS. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	5	3
2" X 2"	8	3
2" X 4"	124	83
2" X 6"	395	395
NAILS	NO. REQ'D	POUNDS
10d (3")	559	9
STEEL STRAPPING, 2" - - - -	348' REQ'D - - - -	116 LBS
STEEL STRAPPING, 1-1/4" - - -	48' REQ'D - - - -	7 LBS
STEEL STRAPPING, 3/4" - - - -	166' REQ'D - - - -	12 LBS
SEAL FOR 2" STRAPPING - - - -	64 REQ'D - - - -	14 LBS
SEAL FOR 1-1/4" STRAPPING - - -	3 REQ'D - - - -	NIL
SEAL FOR 3/4" STRAPPING - - - -	8 REQ'D - - - -	NIL
EDGE PROTECTOR - - - - -	2 REQ'D - - - -	NIL

(KEY NUMBERS CONTINUED)

- ⑮ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQ'D). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIRCLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY N AND SEAL WITH TWO SEALS MARKED ⑮. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑯ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQ'D). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON CENTER GATE ASSEMBLY N. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑯. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑰ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQ'D). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY M. POSITION STRAP ON BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑰. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE "NOTE ●" ON PAGE 41 AND GENERAL NOTE "L" ON PAGE 2.
- ⑱ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQ'D). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AROUND THE TOP STRAPPING BOARD ON CENTER GATE ASSEMBLY M. POSITION STRAP ON BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑱. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE "NOTE ●" ON PAGE 41 AND GENERAL NOTE "L" ON PAGE 2.
- ⑲ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQ'D). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY B AND SEAL WITH TWO SEALS MARKED ⑲. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑳ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQ'D). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A STAKE POCKET OR TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑳. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
- ㉑ EDGE PROTECTOR, STEEL FOR 2" STEEL STRAPPING (2 REQ'D). POSITION UNDER STRAP MARKED ⑮ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE, USE SHORT PIECE OF 2" STEEL STRAPPING.
- ㉒ PAD, 2" X .044" OR .050" BY 24" LENGTH OF STEEL STRAPPING (8 REQ'D). POSITION THROUGH STAKE POCKET UNDER STRAPS MARKED ⑲. SECURE WITH ONE SEAL MARKED ㉒. SEE THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 57.

(CONTINUED AT LEFT)

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
8-INCH CCL - - - - -	1 - - - - -	22,259 LBS
DUNNAGE - - - - -	- - - - -	1,126 LBS
TOTAL WEIGHT - - - - -		23,385 LBS


(KEY NUMBERS CONTINUED)

- ⑨ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN, BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY D AND SEAL WITH TWO SEALS MARKED ⑬. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.

(CONTINUED BELOW)

INDICATES 2 C787
120MM AMMO PALLETS.

INDICATES 8 C786
120MM AMMO PALLETS.



ISOMETRIC VIEW

(KEY NUMBERS CONTINUED)

- ⑩ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATIONS SHOWN, BRING LOOSE ENDS AT AN ANGLE UP AROUND THE STRAPPING BOARD ON END GATE ASSEMBLY D. POSITION STRAPS ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑬. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑪ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (7 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑬. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑫ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ⑦ AT SHARP CORNER OF A-FRAME, IF EDGE PROTECTORS ARE NOT AVAILABLE USE SHORT PIECE OF 2" STEEL STRAPPING.
- ⑬ SEAL FOR 2" STEEL STRAPPING (44 REQD). FOUR SEALS REQUIRED FOR EACH STRAP MARKED ⑦, ⑧, ⑨, ⑩ AND ⑪. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

KEY NUMBERS

- ① END GATE ASSEMBLY C (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 50.
- ② CENTER GATE ASSEMBLY D (1 REQD). POSITION BETWEEN PALLETS AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 42.
- ③ END GATE ASSEMBLY D (1 REQD). POSITION AT THE AFT END OF THE LOAD. SEE THE DETAIL ON PAGE 50.
- ④ HOLD-DOWN ASSEMBLY A, (4 REQD). POSITION ON TOP OF THE PALLETS AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 46.
- ⑤ HOLD-DOWN 2" X 6" BY LENGTH-TO-SUIT (2 REQD). POSITION ON JOINTS BETWEEN PALLETS AT LOCATION SHOWN.
- ⑥ STRAPPING BOARD ASSEMBLY A (7 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ⑤ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑦ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIRCLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY D AND SEAL WITH TWO SEALS MARKED ⑬. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑧ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN, BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE STRAPPING BOARD ON CENTER GATE ASSEMBLY D. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑬. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(CONTINUED AT LEFT)

120MM COMBAT CONFIGURED LOAD

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
C786	CTG, 120MM M829 39.50 L X 44.50 W X 51.50 H	240	8 PALLETS	19,128 LBS
C787	CTG, 120MM M830 40.13 L X 44.50 W X 51.75 H	60	2 PALLETS	4,866 LBS

120MM ARMOR COMBAT CONFIGURED LOAD


SPECIAL NOTES:

1. A TYPICAL 120MM COMBAT CONFIGURED LOAD FOR ARMOR IS SHOWN LOADED ON THE 16-1/2-TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE 120MM COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 24 IS TYPICAL. IF LOADING PALLETIZED UNITS OR OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE 120MM PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. LOADS OF PALLETIZED UNITS, OTHER THAN SEPARATE LOADING PROJECTILES, HAVING A TOTAL WEIGHT OF 16,500 POUNDS OR MORE MUST BE DIVIDED INTO TWO SECTIONS. EACH SECTION MUST BE SECURED WITH A GATE AND STEEL STRAPPING AS SHOWN IN THE LOAD ON PAGE 24. NOTE THAT THE 10 PALLETS SHOWN IN THE LOAD ON PAGE 24 HAVE A TOTAL WEIGHT OF 23,994 POUNDS. THEREFORE, THE LOAD WAS DIVIDED INTO TWO SECTIONS WITH THE FORWARD SECTION WEIGHING 14,346 POUNDS AND THE AFT SECTION WEIGHING 9,648 POUNDS. IF LOADING PALLETIZED UNITS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES. IF LOADING SEPARATE LOADING PROJECTILES, FOLLOW THE PROCEDURES SHOWN ON PAGE 28.
5. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STRAPPING IS IN POSITION.
6. FOR EASE OF LOADING AND SECUREMENT OF THE LOAD, AN EVEN NUMBER OF PALLETIZED UNITS SHOULD BE LOADED ON EACH FLATRACK. IF AN ODD NUMBER OF PALLETIZED UNITS ARE TO BE LOADED, SEE THE LOAD ON PAGE 30 FOR GUIDANCE. ALWAYS POSITION A SINGLE PALLETIZED UNIT BETWEEN TWO FULL ROWS.
7. FOR THE SAME 120MM COMBAT CONFIGURED LOAD ON THE M1 FLATRACK, SEE PAGES 8 AND 9.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	13	7
2" X 4"	155	104
2" X 6"	240	240
NAILS	NO. REQD	POUNDS
6d (2")	32	1/4
10d (3")	361	5-1/2
STEEL STRAPPING, 2" - - - - 262' REQD - - - - 88 LBS		
SEAL FOR 2" STRAPPING - - - - 44 REQD - - - - 9 LBS		
EDGE PROTECTOR FOR 2" STRAPPING-2 REQD - - - - NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
120MM AMMO PLT - - - -	10 - - - - -	23,994 LBS
DUNNAGE - - - - -	- - - - -	805 LBS
TOTAL WEIGHT - - - - -		24,799 LBS



ISOMETRIC VIEW

(KEY NUMBERS CONTINUED)

- ⑪ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK, BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑫. SECURE INTO PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
- ⑫ PAD, 2" X .044" OR .050" BY 24" LENGTH OF STEEL STRAPPING (6 REQD). POSITION THROUGH STAKE POCKET UNDER STRAPS MARKED ⑪ AT LOCATIONS SHOWN. SECURE WITH ONE SEAL MARKED ⑬. SEE THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 57.
- ⑬ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ⑪ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE USE A SHORT PIECE OF 2" STEEL STRAPPING.
- ⑭ SEAL FOR 2" STEEL STRAPPING (38 REQD). SIX SEALS FOR EACH STRAP THREADED THRU THE STAKE POCKETS AND FOUR SEALS FOR EACH STRAP ATTACHED TO TIEDOWN ANCHORS. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

KEY NUMBERS

- ① END GATE ASSEMBLY E (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 51.
- ② END GATE ASSEMBLY F (1 REQD). POSITION AT THE AFT END OF THE LOAD. SEE THE DETAIL ON PAGE 51.
- ③ HOLD-DOWN ASSEMBLY A, (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 46.
- ④ HOLD-DOWN, 2" X 4" BY LENGTH-TO-SUIT (1 REQD). POSITION ON CENTER JOINT BETWEEN LATERALLY ADJACENT PALLETS.
- ⑤ STRAPPING BOARD ASSEMBLY A (4 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ④ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑥ FILLER ASSEMBLY C (1 REQD). POSITION AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 47.
- ⑦ STRAPPING BOARD ASSEMBLY D (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑧ STRAPPING BOARD ASSEMBLY C (2 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑨ LOAD RETAINING STRAP 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIrcLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY F AND SEAL WITH TWO SEALS MARKED ⑭. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑩ LOAD RETAINING STRAP 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN, BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON END GATE ASSEMBLY F. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑭. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(CONTINUED AT LEFT)

COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
PL94	STINGER-MR, FIM 92C 39.37 L X 67.25 W X 36.50 H	36	4 PALLETS	2,996 LBS
PB93	TOW IIA, BGM-71D 48.00 L X 58.25 W X 39.75 H	12	1 PALLET	1,127 LBS
A974	25MM CARTRIDGE, APOS-T, M791 31.50 L X 45.00 W X 42.50 H	600	1 PALLET	1,241 LBS
A975	25MM CARTRIDGE, HEI-T, M792 31.50 L X 45.00 W X 42.50 H	1,200	2 PALLETS	2,482 LBS

COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY

SPECIAL NOTES:

1. A TYPICAL COMBAT CONFIGURED LOAD FOR AIR DEFENSE ARTILLERY IS SHOWN LOADED ON THE 16-1/2-TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE COMBAT CONFIGURED LOAD SHOWN IN THE CHART ON PAGE 26 IS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally and Longitudinally TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER THE HOLD-DOWN STRAPPING IS IN POSITION.
5. FOR THE SAME COMBAT CONFIGURED LOAD ON THE M1 FLATRACK, SEE PAGES 10 AND 11.


BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	8	4
2" X 2"	9	3
2" X 4"	127	85
2" X 6"	210	210
NAILS	NO. REQD	POUNDS
6d (2")	16	NIL
10d (3")	358	5-1/2
STEEL STRAPPING. 2" - - - - 266' REQD - - - - 89 LBS		
SEAL FOR 2" STRAPPING - - - - 38 REQD - - - - 8 LBS		
EDGE PROTECTOR FOR 2" STRAPPING-2 REQD - - - - NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
CCL - - - - -	1 - - - - -	7,846 LBS
DUNNAGE - - - - -	- - - - -	707 LBS
TOTAL WEIGHT - - - - -		8,553 LBS

(KEY NUMBERS CONTINUED)

- ⑪ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON CENTER GATE ASSEMBLY P. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑫. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.



(KEY NUMBERS CONTINUED)

- ⑫ BUNDLING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP TO ENCIRCLE TWO LONGITUDINALLY ADJACENT PALLET UNITS, CENTER GATE ASSEMBLY Q, AND END GATE ASSEMBLY H. POSITION STRAPS AROUND CENTERS OF THE THIRD PALLET FROM EACH SIDE, UNDER SKIDS AND OVER TOP OF COVER. PRE-POSITION STRAPS ON FLOOR OF FLATRACK PRIOR TO LOADING THE TWELVE PALLET UNITS AT THE AFT END. POSITION STRAPS UNDER THE STRAPPING BOARDS MARKED ⑦ AND SEAL WITH ONE SEAL MARKED ⑬. SEE SPECIAL NOTE 7 ON PAGE 29 AND GENERAL NOTE "M" ON PAGE 2.
- ⑬ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY Q AND SEAL WITH TWO SEALS MARKED ⑭. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE SPECIAL NOTE 7 ON PAGE 29 AND GENERAL NOTE "L" ON PAGE 2.
- ⑭ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON CENTER GATE ASSEMBLY Q. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑮. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE SPECIAL NOTE 7 ON PAGE 29 AND GENERAL NOTE "L" ON PAGE 2 AND THE STRAP THREADING DETAIL ON PAGE 56.

(KEY NUMBERS CONTINUED ON PAGE 29)

KEY NUMBERS

- ① END GATE ASSEMBLY G (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 52.
- ② CENTER GATE ASSEMBLY P (1 REQD). POSITION BETWEEN PALLET'S AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 43.
- ③ CENTER GATE ASSEMBLY Q (1 REQD). POSITION BETWEEN PALLET'S AT LOCATION SHOWN. SEE THE DETAIL ON PAGE 43, AND SPECIAL NOTE 7 ON PAGE 29.
- ④ END GATE ASSEMBLY H (1 REQD). POSITION AT AFT END OF LOAD. SEE THE DETAIL ON PAGE 52.
- ⑤ HOLD-DOWN ASSEMBLY B (6 REQD). POSITION ON TOP OF THE PALLET'S AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ⑥ HOLD-DOWN, 2" X 4" X 58" (6 REQD). POSITION ON JOINTS BETWEEN PALLET'S AT LOCATIONS SHOWN.
- ⑦ STRAPPING BOARD ASSEMBLY A (8 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ⑥ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑧ UNITIZING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (12 REQD). INSTALL EACH STRAP TO ENCIRCLE THREE LATERALLY ADJACENT PALLET UNITS UNDER THE SKID BASE AND OVER TOP OF COVER. THESE STRAPS MAY BE POSITIONED PRIOR TO LOADING PALLET'S ON THE FLATRACK. SEAL WITH ONE SEAL MARKED ⑨. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑨ BUNDLING STRAP, 1-1/4" X .035" OR .031" BY LENGTH-TO-SUIT STEEL STRAPPING (12 REQD). INSTALL EACH STRAP TO ENCIRCLE SIX LATERALLY ADJACENT PALLET UNITS UNDER THE SKID BASE AND OVER TOP OF COVER (6 REQD). POSITION STRAPS AT CENTER OF PALLET'S. SEAL WITH ONE SEAL MARKED ⑩. SEE GENERAL NOTE "M" ON PAGE 2.
- ⑩ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIRCLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY P. SEAL WITH TWO SEALS MARKED ⑪. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.

120MM COMPLETE ROUND CONFIGURED LOAD

ODDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
0563	PROJ, 155MM, M483A1 DPICM 14.62 L X 29.12 W X 39.38 H	288	36 PALLET'S	31,464 LBS

155MM SEPARATE LOADING PROJECTILES

(CONTINUED AT LEFT)

SPECIAL NOTES:

1. A TYPICAL LOAD OF 36 PALLETES OF 155MM SEPARATE LOADING PROJECTILES IS SHOWN LOADED ON THE 16-1/2-TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE 155MM SLP (D563) EIGHT PROJECTILE PALLET HAVING DIMENSIONS OF 29-1/8" WIDE BY 14-5/8" LONG BY 39-3/8" HIGH AND WEIGHING 874 POUNDS IS SHOWN AS TYPICAL. IF LOADING SEPARATE LOADING PROJECTILES OF OTHER QUANTITIES, DIMENSIONS, AND WEIGHT, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE SLP PALLETES, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. DUE TO WEIGHT, HIGH CENTER OF GRAVITY, AND SMALL SKID AREA CONTACTING THE STEEL FLOOR, LOADS OF SEPARATE LOADING PROJECTILES MUST BE DIVIDED INTO SECTIONS WHICH NOT EXCEED 11,000 POUNDS. EACH SECTION MUST BE SECURED WITH A GATE AND STEEL STRAPPING AS SHOWN IN THE LOAD ON PAGE 28. NOTE THAT THE 36 PALLETES SHOWN IN THE LOAD ON PAGE 28 HAVE A TOTAL WEIGHT OF 31,464 POUNDS. THEREFORE, THE LOAD WAS DIVIDED INTO THREE SECTIONS WEIGHING 10,488 POUNDS EACH.
5. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER HOLD-DOWN STEEL STRAPPING IS IN POSITION.
6. FOR EASE OF LOADING AND SECUREMENT OF THE LOAD, EACH ROW OF SEPARATE LOADING PROJECTILES POSITIONED ACROSS THE WIDTH OF THE FLATRACK MUST CONTAIN THE SAME QUANTITY. USE AN "OMITTED SLP PALLETIZED UNIT ASSEMBLY" FOR EACH OMITTED UNIT AS NECESSARY TO MAINTAIN ROWS. SEE THE "OMITTED SLP PALLETIZED UNIT ASSEMBLY" DETAIL ON PAGE 58.
7. STRAPS MARKED ⑫ MUST BE PRE-POSITIONED ON THE FLOOR OF FLATRACK AND AROUND CENTER GATE ASSEMBLY Q PRIOR TO INSTALLING STRAPS MARKED ⑬ AND ⑭, AND THE LAST TWO ROWS OF SEPARATE LOADING PROJECTILE PALLETES. POSITION STRAPS MARKED ⑫ TO CENTER ON THE THIRD PALLET FROM EACH SIDE OF THE FLATRACK. STRAPS MARKED ⑫ ARE REQUIRED TO HELP RETAIN THE CENTER ROWS OF PALLETES DURING AFT END IMPACT.
8. TWO LOAD RETAINING STRAPS MARKED ⑮ AND TWO LOAD RETAINING STRAPS MARKED ⑯ ARE REQUIRED AT THE AFT END OF THE LOAD DUE TO THE MAXIMUM LOAD WEIGHT AND SMALL SKID AREA OF THE 155MM SLP PALLETES.
9. FOR THE SAME ITEM ON THE M1 FLATRACK SEE PAGES 16 AND 17.

(KEY NUMBERS CONTINUED)


- ⑮ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATIONS SHOWN. INSTALL THE SHORTEST STRAPS FIRST THEN THE LONGER STRAPS OVER TOP OF SHORT STRAPS AND TO DIFFERENT TIEDOWN ANCHORS. BRING LOOSE END AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY H AND SEAL WITH TWO SEALS PIECES MARKED ②①. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND SPECIAL NOTE 8 ON THIS PAGE.
- ⑯ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (2 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATIONS SHOWN. INSTALL THE SHORTEST STRAPS FIRST THEN THE LONGER STRAPS OVER TOP OF SHORT STRAPS AND TO DIFFERENT TIEDOWN ANCHORS. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON END GATE ASSEMBLY H. POSITION STRAPS ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ②①. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND SPECIAL NOTE 8 ON THIS PAGE.
- ⑰ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A STAKE POCKET OR TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS PIECES MARKED ②①. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAILS ON PAGES 56 AND 57.
- ⑱ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ⑮ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE USE A SHORT PIECE OF 2" STEEL STRAPPING.
- ⑲ PAD, 2" X .044" OR .050" X 24" LENGTH OF STEEL STRAPPING (12 REQD). POSITION THROUGH STAKE POCKET UNDER STRAPS MARKED ⑰. SECURE WITH ONE SEAL MARKED ②①. SEE THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 57.
- ⑳ SEAL FOR 1-1/4" STEEL STRAPPING (20 REQD). ONE SEAL FOR EACH STRAP MARKED ⑧, ⑨, ⑫. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "M" ON PAGE 2.
- ㉑ SEAL FOR 2" STEEL STRAPPING (76 REQD). SIX SEALS FOR EACH STRAP THREADED THRU STAKE POCKETS AND FOUR SEALS FOR EACH STRAP ATTACHED TO TIEDOWN ANCHORS. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

BILL OF MATERIAL

LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	5	3
2" X 2"	8	3
2" X 4"	169	113
2" X 6"	322	322
NAILS	NO. REQD	POUNDS
6d (2")	11	1/4
10d (3")	511	8
STEEL STRAPPING, 1-1/4" -- 344' REQD --- 50 LBS		
STEEL STRAPPING, 2" --- 460' REQD --- 154 LBS		
SEAL FOR 1-1/4" STRAPPING -- 20 REQD --- 17 LBS		
SEAL FOR 2" STRAPPING --- 76 REQD --- 12 LBS		
EDGE PROTECTOR FOR 2" STRAPPING-2 REQD --- NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
155 MM SLP PLTS	36	31,464 LBS
DUNNAGE		1,108 LBS
TOTAL WEIGHT		32,572 LBS



ISOMETRIC VIEW

KEY NUMBERS

- (KEY NUMBERS CONTINUED)
- ⑧ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (10 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A STAKE POCKET OR TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑪. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
 - ⑨ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ⑥ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE USE A SHORT PIECE OF 2" STEEL STRAPPING.
 - ⑩ PAD, 2" X .044" OR .050" BY 24" LENGTH OF STEEL STRAPPING (2 REQD). POSITION THROUGH STAKE POCKET UNDER STRAP MARKED ⑧. SECURE WITH ONE SEAL MARKED ⑪. SEE THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 57.
 - ⑪ SEAL FOR 2" STEEL STRAPPING (50 REQD). SIX SEALS FOR THE STRAP THREADED THRU THE STAKE POCKETS AND FOUR SEALS FOR EACH STRAP ATTACHED TO TIEDOWN ANCHORS. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.
 - ① END GATE ASSEMBLY J (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 53.
 - ② END GATE ASSEMBLY K (1 REQD). POSITION AT AFT END OF LOAD. SEE THE DETAIL ON PAGE 53.
 - ③ STRAPPING BOARD ASSEMBLY F (8 REQD). POSITION AT THE LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
 - ④ STRAPPING BOARD ASSEMBLY A (2 REQD). POSITION AT THE LOCATIONS SHOWN AND NAIL TO THE HOLD-DOWN PIECES MARKED ⑤ W/2-10d NAILS EACH END. SEE THE DETAIL ON PAGE 44.
 - ⑤ HOLD-DOWN ASSEMBLY A (2 REQD). POSITION ON TOP OF THE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
 - ⑥ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIrcLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY K AND SEAL WITH TWO SEALS MARKED ⑪. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
 - ⑦ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON END GATE ASSEMBLY K. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑪. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(KEY NUMBERS CONTINUED AT LEFT)

TYPICAL AMMUNITION ITEMS

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
0541	PROP CHARGE 155MM M4 55.00 L X 40.00 W X 44.88 H	350	7 PALLETS	12,362 LBS

155MM PROPELLING CHARGE CONTAINERS


SPECIAL NOTES:

1. A TYPICAL LOAD OF 7 PALLETS OF 155MM PROPELLING CHARGE CONTAINERS IS SHOWN LOADED ON THE 16-1/2-TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE 155MM PROPELLING CHARGE (0541) PACKED IN THE M13 SERIES CONTAINER, 50 CONTAINERS PER PALLET HAVING DIMENSIONS OF 40" LONG BY 55" WIDE BY 44-7/8" HIGH AND WEIGHING 1,766 POUNDS, IS SHOWN AS TYPICAL. IF LOADING PALLETIZED UNITS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE 155MM PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. LOADS OF METAL AND/OR WOOD PALLETIZED UNITS, OTHER THAN SEPARATE LOADING PROJECTILES, HAVING A TOTAL WEIGHT OF 16,500 POUNDS OR MORE MUST BE DIVIDED INTO TWO SECTIONS, EACH SECTION MUST BE SECURED WITH A GATE AND STEEL STRAPPING AS SHOWN IN THE LOAD ON PAGE 28. NOTE THAT THE 7 PALLETS SHOWN IN THE LOAD ON PAGE 30 HAVE A TOTAL WEIGHT OF 12,362 POUNDS, THEREFORE, THE LOAD WAS NOT DIVIDED. IF LOADING PALLETIZED UNITS OF OTHER ITEMS, SIZES, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES. IF LOADING SEPARATE LOADING PROJECTILES FOLLOW THE PROCEDURES SHOWN ON PAGE 28.
5. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER HOLD-DOWN STEEL STRAPPING IS IN POSITION.
6. FOR EASE OF LOADING AND SECUREMENT OF THE LOAD, AN EVEN NUMBER OF PALLETIZED UNITS SHOULD BE LOADED ON EACH FLATRACK. HOWEVER, DUE TO THE SIZE OF THE PALLETIZED UNIT SHOWN IN THE LOAD ON PAGE 30, IT WAS NECESSARY TO LOAD AN ODD NUMBER OF PALLETIZED UNITS WITH ONE PALLETIZED UNIT POSITIONED WITH THE 40" DIMENSION PARALLEL TO THE SIDE OF THE FLATRACK, IN ORDER TO ACHIEVE A MAXIMUM LOAD.
7. FOR THE SAME ITEM LOADED ON THE M1 FLATRACK SEE PAGES 18 AND 19.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
2" X 4"	97	65
2" X 6"	179	179
NAILS	NO. REQD	POUNDS
10d (3")	370	6
STEEL STRAPPING, 2" - - - - - 308' REQD - - - 103 LBS		
SEAL FOR 2" STRAPPING - - - - - 50 REQD - - - 11 LBS		
EDGE PROTECTOR FOR 2" STRAPPING - 2 REQD - - - NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
155MM PROP CHARGE		
PALLET - - - - -	7 - - - - -	12,362 LBS
DUNNAGE - - - - -	- - - - -	608 LBS
TOTAL WEIGHT - - - - -		12,970 LBS



KEY NUMBERS

- ① END GATE ASSEMBLY L (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 54.
- ② CENTER GATE ASSEMBLY R (1 REQD). POSITION BETWEEN THE SEPARATE LOADING PROJECTILE PALLETS AND THE PROPELLING CHARGE PALLETS. SEE THE DETAIL ON PAGE 44.
- ③ END GATE ASSEMBLY M (1 REQD). POSITION AT AFT END OF LOAD. SEE THE DETAIL ON PAGE 54.
- ④ HOLD-DOWN ASSEMBLY B (2 REQD). POSITION ON TOP OF THE SEPARATE LOADING PROJECTILE PALLETS AS SHOWN. SEE THE DETAIL ON PAGE 46.
- ⑤ HOLD-DOWN, 2" X 4" X 56" (1 REQD). POSITION ON CENTER JOINT BETWEEN SEPARATE LOADING PROJECTILE PALLETS.
- ⑥ STRAPPING BOARD ASSEMBLY A (3 REQD). POSITION ON TOP OF THE SEPARATE LOADING PROJECTILE PALLETS AT LOCATIONS SHOWN. NAIL TO THE HOLD-DOWN PIECE MARKED ⑤ W/2-10d NAILS EACH JOINT. SEE THE DETAIL ON PAGE 44.
- ⑦ STRAPPING BOARD ASSEMBLY E (6 REQD). POSITION ON TOP OF THE PROPELLING CHARGE PALLETS AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ⑧ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIRCLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON CENTER GATE ASSEMBLY R AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑨ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON CENTER GATE ASSEMBLY R. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑩.

(KEY NUMBERS CONTINUED)

SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

- ⑩ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY M AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.

(KEY NUMBERS CONTINUED ON PAGE 33)

TYPICAL AMMUNITION ITEMS

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
D680	PROJ, 8-INCH 19.25 L X 28.00 W X 40.38 H	48	8 PALLETS	10,024 LBS
D676	PROP CHARGE, 8-INCH 58.50 L X 40.75 W X 46.25 H	128	4 PALLETS	7,512 LBS

(CONTINUED AT LEFT)

SPECIAL NOTES:

1. A TYPICAL LOAD OF 8 PALLETS OF 8-INCH SLP AND 4 PALLETS OF 8-INCH PROP CHARGE ARE SHOWN LOADED ON THE 15-1/2-TON A-FRAME FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19'-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE ITEMS SHOWN IN THE CHART ON PAGE 32 ARE SHOWN AS TYPICAL. IF LOADING PALLETS OF OTHER ITEMS, QUANTITIES, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE PALLETS, ASSURE THAT ALL STEEL STRAPPING ON EACH PALLET IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL PALLET UNITS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER Laterally AND LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER HOLD-DOWN STRAPPING IS IN POSITION.
5. FOR EASE OF LOADING AND SECUREMENT OF THE LOAD EACH ROW OF SEPARATE LOADING PROJECTILES POSITIONED ACROSS THE WIDTH OF THE FLATRACK MUST CONTAIN THE SAME QUANTITY. USE AN "OMITTED SLP PALLETIZED UNIT ASSEMBLY" FOR EACH OMITTED SLP PALLETIZED UNIT AS NECESSARY TO MAINTAIN EVEN ROWS. SEE THE "OMITTED SLP PALLET UNIT ASSEMBLY" DETAIL ON PAGE 58.

(KEY NUMBERS CONTINUED FROM PAGE 32)


- ⑪ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLATRACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON END GATE ASSEMBLY M, POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑫ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (3 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A STAKE POCKET ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD MARKED ⑥ AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
- ⑬ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (6 REQD). INSTALL STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A STAKE POCKET OR TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD MARKED ⑦ AND SEAL WITH TWO SEALS MARKED ⑩. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
- ⑭ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ⑧ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE USE A SHORT PIECE OF 2" STEEL STRAPPING.
- ⑮ PAD, 2" X .044" OR .050" BY 24" LENGTH OF STEEL STRAPPING (6 REQD). POSITION THROUGH STAKE POCKET UNDER STRAP MARKED ⑫ AND ⑬ IF APPLICABLE. SECURE WITH ONE SEAL MARKED ⑩. SEE THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑯ SEAL FOR 2" STEEL STRAPPING (58 REQD). FOUR SEALS FOR EACH STRAP MARKED ⑧, ⑨, ⑪, ⑫ AND ⑬, AND SIX SEALS FOR EACH STRAP MARKED ⑭. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

BILL OF MATERIAL

LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	5	3
2" X 2"	8	3
2" X 4"	106	71
2" X 6"	277	277
NAILS	NO. REQD	POUNDS
6d (2")	11	1/4
10d (3")	463	7-1/4
STEEL STRAPPING, 2" - - - - - 372' REQD - - - 124 LBS		
SEAL FOR 2" STRAPPING - - - - - 58 REQD - - - 12 LBS		
EDGE PROTECTOR FOR 2" STRAPPING - 2 REQD - - - NIL		

LOAD AS SHOWN

ITEM	QUANTITY	WEIGHT (APPROX)
8-INCH SLP PALLET-	8	10,024 LBS
8-INCH PC PALLET	4	7,512 LBS
DUNNAGE		852 LBS
TOTAL WEIGHT		18,388 LBS



KEY NUMBERS

- ① END GATE ASSEMBLY N (1 REQD). POSITION AT THE FORWARD END OF THE LOAD. SEE THE DETAIL ON PAGE 55.
- ② END GATE ASSEMBLY O (1 REQD). POSITION AT AFT END OF LOAD. SEE THE DETAIL ON PAGE 55.
- ③ STRAPPING BOARD ASSEMBLY C (8 REQD). POSITION AT LOCATIONS SHOWN. SEE THE DETAIL ON PAGE 45.
- ④ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ENCIRCLING THE STEEL FRAME ON EACH SIDE OF THE A-FRAME, APPROXIMATELY 7" ABOVE THE FLOOR. BRING LOOSE ENDS AROUND THE BOTTOM STRAPPING BOARD ON END GATE ASSEMBLY O AND SEAL WITH TWO SEALS MARKED ⑧. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2.
- ⑤ LOAD RETAINING STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (1 REQD). INSTALL IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A FLAT-RACK TIEDOWN ANCHOR AT LOCATION SHOWN. BRING LOOSE ENDS AT AN ANGLE UP AND AROUND THE TOP STRAPPING BOARD ON END GATE ASSEMBLY O. POSITION STRAP ON THE BEVELED SURFACE AND SEAL WITH TWO SEALS MARKED ⑧. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGE 56.
- ⑥ HOLD-DOWN STRAP, 2" X .044" OR .050" BY LENGTH-TO-SUIT STEEL STRAPPING (8 REQD). INSTALL EACH STRAP IN TWO PIECES WITH ONE END OF EACH PIECE ATTACHED TO A TIEDOWN ANCHOR ON SIDE OF FLATRACK. BRING LOOSE ENDS UP OVER TOP OF STRAPPING BOARD AND SEAL WITH TWO SEALS MARKED ⑧. SECURE IN PLACE BY DRIVING 10d NAILS INTO THE STRAPPING BOARD ON EACH SIDE OF THE STRAP AND BENDING OVER STRAP. STAPLES MAY BE USED IF AVAILABLE. SEE GENERAL NOTE "L" ON PAGE 2 AND THE HOLD-DOWN STRAP THREADING DETAIL ON PAGES 56 AND 57.
- ⑦ EDGE PROTECTOR, STEEL, FOR 2" STEEL STRAPPING (2 REQD). POSITION UNDER STRAP MARKED ④ AT SHARP CORNER OF A-FRAME. IF EDGE PROTECTORS ARE NOT AVAILABLE USE A SHORT PIECE OF 2" STEEL STRAPPING.
- ⑧ SEAL FOR 2" STEEL STRAPPING (40 REQD). FOUR SEALS FOR EACH STRAP MARKED ④, ⑤ AND ⑥. DOUBLE CRIMP EACH SEAL. SEE GENERAL NOTE "L" ON PAGE 2.

TYPICAL AMMUNITION ITEMS

DDIC	ITEM	ITEM QUANTITY	LOAD QUANTITY	TOTAL WEIGHT
M913	CHARGE, DEMO M58A3 83.25 L X 53.75 W X 24.75 H	4	4 CNTRS	11,600 LBS

M58A3 LINEAR DEMOLITION CHARGE (MICLIC)


SPECIAL NOTES:

1. A TYPICAL LOAD OF FOUR MS8A3 DEMOLITION CHARGES IS SHOWN LOADED ON THE 16-1/2 TON M1077 FLATRACK HAVING CARGO DECK DIMENSIONS OF 7'-6-1/2" WIDE BY 19-0" LONG AND A MAXIMUM LOAD WEIGHT OF 33,000 POUNDS.
2. THE MS8A3 DEMOLITION CHARGE, IN METAL CONTAINERS HAVING DIMENSIONS OF 53-3/4" WIDE BY 6'-11-1/4" LONG BY 24-3/4" HIGH AND WEIGHING 2900 POUNDS, IS SHOWN AS TYPICAL. IF LOADING SIMILAR TYPE CONTAINERS OF OTHER ITEMS, DIMENSIONS, AND WEIGHTS, FOLLOW THESE SAME PROCEDURES AS CLOSELY AS POSSIBLE.
3. PRIOR TO LOADING THE CONTAINERS, ASSURE THAT ALL STEEL STRAPPING ON EACH CONTAINER IS IN POSITION AND IS TIGHT. MISSING AND/OR LOOSE STEEL STRAPPING SHOULD BE REPLACED.
4. WHEN LOADING THE FLATRACK, POSITION THE LOAD TIGHT AGAINST THE A-FRAME AT THE FORWARD END OF THE FLATRACK. ALL CONTAINERS MUST BE POSITIONED TIGHTLY AGAINST EACH OTHER LONGITUDINALLY TO REDUCE LOAD MOVEMENT AND ASSURE A TIGHT LOAD AFTER HOLD-DOWN STEEL STRAPPING IS IN POSITION.

BILL OF MATERIAL		
LUMBER	LINEAR FEET	BOARD FEET
1" X 6"	5	3
2" X 4"	78	52
2" X 6"	106	106
NAILS	NO. REQD	POUNDS
6d (2")	11	NIL
10d (3")	189	3
STEEL STRAPPING, 2" - - - - - 311' REQD - - - 104 LBS		
SEAL FOR 2" STRAPPING - - - - - 40 REQD - - - 8 LBS		
EDGE PROTECTOR FOR 2" STRAPPING - 2 REQD - - - NIL		

LOAD AS SHOWN


ITEM	QUANTITY	WEIGHT (APPROX)
MS8A3 LINEAR DEMOLITION		
CHARGE - - - - -	4 - - - - -	11,600 LBS
DUNNAGE - - - - -	- - - - -	437 LBS
TOTAL WEIGHT - - - - -		12,037 LBS



CENTER GATE ASSEMBLY A

USED IN THE LOAD ON PAGE 4.



ASSURE THAT EACH VERTICAL PIECE IS IN LONGITUDINAL ALIGNMENT WITH THE LOAD BEARING PIECES ON CENTER GATE ASSEMBLY B.



CENTER GATE ASSEMBLY B

USED IN THE LOAD ON PAGE 4.


ASSURE THAT EACH LOAD BEARING PIECE IS CENTERED ON THE THREE 3" X 4" INTERMEDIATE DUNNAGE PIECES BETWEEN PROP CHARGE CONTAINERS.



CENTER GATE ASSEMBLY C

USED IN THE LOAD ON PAGE 6.


1" THICK MATERIAL MAY BE USED IF CENTER OF LOAD SPACE IS 3" OR LESS. ALSO, ADDITIONAL MATERIAL MAY BE LAMINATED TO THE LOAD BEARING PIECES IF CENTER OF LOAD SPACE IS GREATER THAN 3".



CENTER GATE ASSEMBLY D


USED IN THE LOAD ON PAGE 8.

DETAILS




CENTER GATE ASSEMBLY E

USED IN THE LOAD ON PAGE 10. ADDITIONAL 6" WIDE BY THICKNESS-TO-SUIT MATERIAL MAY BE LAMINATED TO THE LOAD BEARING PIECES IF REQUIRED TO ASSURE A TIGHT LOAD.




CENTER GATE ASSEMBLY F


USED IN THE LOAD ON PAGE 12.




CENTER GATE ASSEMBLY G
USED IN THE LOAD ON PAGE 14.





CENTER GATE ASSEMBLY H
USED IN THE LOAD ON PAGE 14.





CENTER GATE ASSEMBLY J
(2 REQD)



CENTER GATE ASSEMBLY K
USED IN THE LOAD ON PAGE 18. IF DESIRED, 48" WIDE BY 6'-8" LONG BY THICKNESS-TO-SUIT PLYWOOD SHEETS MAY BE USED IN LIEU OF THE CENTER GATE SHOWN ABOVE.



DETAILS




VERTICAL PIECE, 2" X 6" X 43"
(DOUBLED) (6 REQD). LAMINATE
THE FIRST PIECE TO THE SECOND
PIECE W/5-10d NAILS.

SUPPORT PIECE, 2" X 6"
BY CUT-TO-FIT BETWEEN
TOP AND BOTTOM STRAPPING
BOARDS (6 REQD). NAIL
TO VERTICAL PIECE
W/5-10d NAILS.

STRAPPING BOARD, 2" X 6"
X 6'-5" (2 REQD). NAIL
TO THE VERTICAL PIECES
W/3-10d NAILS EACH JOINT.
BEVEL THE TOP PIECE AS
SHOWN IN THE "TOP STRAPPING
BOARD DETAIL" ON PAGE 48.

POSITION THIS SIDE
AGAINST THE PROP
CHARGE PALLET.




HORIZONTAL PIECE, 2" X 6"
X 6'-5" (DOUBLED) (2 REQD).
NAIL FIRST PIECE TO THE VERTICAL
PIECES W/3-10d NAILS EACH JOINT.
NAIL SECOND PIECE TO THE FIRST
PIECE W/1-10d NAIL EVERY 8".

CENTER GATE ASSEMBLY R
USED IN THE LOAD ON PAGE 32.

STRAPPING BOARD, 2" X 4" X
LOAD WIDTH (1 REQD). DO NOT
EXTEND PAST THE EDGE OF
HOLD-DOWN ASSEMBLY ON EACH
SIDE OF THE LOAD.


PURCHASE BOARD, 2" X 4"
X 24" (1 REQD). NAIL TO
THE STRAPPING BOARD
W/4-10d NAILS.



STRAPPING BOARD ASSEMBLY A

STRAPPING BOARD, 2" X 4" X
LOAD WIDTH PLUS 3" (1 REQD).
DO NOT EXTEND PAST THE EDGE
OF HOLD-DOWN ASSEMBLY ON EACH
SIDE OF THE LOAD.

PURCHASE BOARD, 2" X 4"
X 32" (1 REQD). NAIL TO
THE STRAPPING BOARD
W/4-10d NAILS.




STRAPPING BOARD ASSEMBLY C

STRAPPING BOARD, 2" X 4" X
LOAD WIDTH (1 REQD).

PURCHASE BOARD, 2" X 4"
X 32" (1 REQD). NAIL TO
THE STRAPPING BOARD
W/4-10d NAILS.

FILL PIECE, 2" X 4" X 57"
(DOUBLED). NAIL FIRST
PIECE TO STRAPPING BOARD
W/5-10d NAILS. NAIL SECOND
PIECE IN A LIKE MANNER.




STRAPPING BOARD ASSEMBLY D

USED IN THE LOAD ON PAGE 10 AND 26.
NOTE THAT THE A974 25MM PALLET IS
2-3/4" HIGHER THAN THE PB93 TOW PALLET.

STRAPPING BOARD, 2" X 4"
X 57" (1 REQD).

PURCHASE BOARD, 2" X 4"
X 18" (1 REQD). NAIL TO
THE STRAPPING BOARD
W/4-10d NAILS.




STRAPPING BOARD ASSEMBLY E

STRAPPING BOARD, 2" X 4" X
LOAD WIDTH (1 REQD).


PURCHASE BOARD, 2" X 4"
X 32" (1 REQD). NAIL TO
THE STRAPPING BOARD
W/4-10d NAILS.

SOLID FILL AS REQUIRED TO
FILL THE VOID SPACE BETWEEN
THE STRAPPING BOARD AND TOP OF
SHORTER PALLET (4 PIECES OF
2" X 4" AND 1 PIECE OF 1" X 4").
NAIL FIRST PIECE TO STRAPPING
BOARD W/5-10d NAILS. NAIL EACH
ADDITIONAL PIECE IN A LIKE MANNER.




STRAPPING BOARD ASSEMBLY F


USED IN THE LOAD ON PAGE 20.
FOR USE ON LATERALLY ADJACENT
PALLET OF DIFFERENT HEIGHTS.



HOLD-DOWN ASSEMBLY A




HOLD-DOWN ASSEMBLY B




FILLER ASSEMBLY A

USED IN THE LOAD ON PAGE 6. REQUIRED TO HOLD-DOWN BUNDLE OF NINE M762 FUZE BOXES.



FILLER ASSEMBLY B

USED IN THE LOAD ON PAGE 26. POSITION THIS ASSEMBLY ON TOP OF THE 25MM CARTRIDGE PALLET FOR VERTICAL HOLD-DOWN.



POSITION THIS SIDE AGAINST THE 25MM PALLET.

FILLER ASSEMBLY C

USED IN THE LOAD ON PAGE 26. REQUIRED TO FILL VOID SPACE BETWEEN PALLETS FOR A LONGITUDINALLY TIGHT LOAD.

TIE-PIECE, 2" X 4" X 13"
(1 REQD). NAIL TO 2"
THICK LOAD BEARING PIECES
W/3-10d NAILS EACH END.

LOAD BEARING PIECE,
1" X 4" X 31" (2 REQD).
NAIL TO THE FILLER
AND TIE PIECES
W/4-10d NAILS.


FILLER PIECE, 2" X 4"
X 27-1/2" (2 REQD).
NAIL TO THE 2" X 4"
LOAD BEARING PIECE
W/4-10d NAILS.

LOAD BEARING PIECE,
2" X 4" X 31"
(2 REQD).

HOLD-DOWN PIECE, 2" X 2" X
13" (1 REQD). NAIL TO LOAD
BEARING PIECES W/2-10d NAILS
EACH END.

SPACER ASSEMBLY A

USED IN THE LOAD ON PAGE 6. NOTE THAT THE
D544 PALLETS ARE 27.13" LONG AND THE D563
ARE 29.12" LONG SO A LONGITUDINAL FILL IS
REQUIRED. POSITION ONE SPACER ASSEMBLY
BETWEEN THE FIRST AND SECOND D544 PALLETS
AND ONE SPACER ASSEMBLY BETWEEN THE THIRD
AND FOURTH D544 PALLETS.



END VIEW

TOP STRAPPING BOARD DETAIL

USED ON THE CENTER AND END GATES. TO
PROVIDE A BEARING SURFACE FOR 2" STEEL
STRAPPING POSITIONED AT AN ANGLE OF
APPROXIMATELY 30°.

LOAD BEARING PIECE, 2"
X 6" X 39" (3 REQD).
(3 REQD). NAIL TO
TIE PIECES W/3-10d
NAILS AT EACH JOINT.


TIE PIECE, 2" X 6"
X 38" (3 REQD).

LOAD BEARING PIECE, 2" X 6" X 39"
(DOUBLED) (3 REQD). NAIL THE
FIRST PIECE TO THE TIE PIECES
W/3-10d NAILS AT EACH JOINT.
NAIL THE SECOND PIECE TO THE
FIRST PIECE W/5-10d NAILS.


HOLD-DOWN PIECE, 2" X 2" X 38"
(1 REQD). NAIL TO LOAD BEARING
PIECES W/2-10d NAILS EACH JOINT.

SPACER ASSEMBLY B

USED IN THE LOAD ON PAGE 12.






END GATE ASSEMBLY A
USED IN THE LOAD ON PAGE 22.



END GATE ASSEMBLY B
USED IN THE LOAD ON PAGE 22.


DETAILS





END GATE ASSEMBLY E



USED IN THE LOAD ON PAGE 26.




END GATE ASSEMBLY F


USED IN THE LOAD ON PAGE 26.

DETAILS






END GATE ASSEMBLY J
USED IN THE LOAD ON PAGE 30.




END GATE ASSEMBLY K
USED IN THE LOAD ON PAGE 30.



DETAILS




END GATE ASSEMBLY L
USED IN THE LOAD ON PAGE 32.



END GATE ASSEMBLY M
USED IN THE LOAD ON PAGE 32.




DETAILS



SIDE VIEW

**HOLD-DOWN STRAP THREADING DETAIL
FOR THE M1 AND/OR A-FRAME FLATRACK**


THREAD ONE END OF THE 2" STEEL STRAPPING UNDER THE CENTER BAR OF THE TIEDOWN ANCHOR ON THE M1 FLATRACK AS SHOWN, OR THREAD ONE END OF THE 2" STEEL STRAPPING THROUGH THE STRAPPING SLOT OF THE TIEDOWN ANCHOR ON THE M1077 FLATRACK. BEND A LENGTH OF APPROXIMATELY 18" UP AND SLIDE ONE 2" STRAP SEAL DOWN OVER END AND DOUBLE CRIMP SEAL. WHEN RATCHETING THE 2" STEEL STRAPPING TIGHT ASSURE THAT THE TIEDOWN ANCHOR IS IN THE UP POSITION, NOT BINDING ON ANYTHING, AND IN STRAIGHT ALIGNMENT WITH THE PULL OF THE STRAP. NOTE THAT THE DESIGN OF THE DESIGN OF THE TIEDOWN ANCHOR ALLOWS IT TO SWIVEL SO 2" STEEL STRAPPING CAN BE POSITIONED STRAIGHT OVER TOP OF LOAD OR AT AN ANGLE TO RETAIN THE LOAD LONGITUDINALLY. THE TIEDOWN ANCHOR FOR THE M1 FLATRACK IS SHOWN. HOWEVER, THE SAME PROCEDURE CAN BE USED FOR THE TIEDOWN ANCHOR ON THE M1077 FLATRACK.



HOLD-DOWN STRAP THREADING DETAIL

FOR THE M1077 FLATRACK

THREAD A 24" LENGTH OF 2" STEEL STRAPPING THROUGH THE STAKE POCKET TO PROVIDE A PAD AT SHARP EDGE OF STAKE HOLDING TAB. THREAD ONE END OF THE 2" STEEL HOLD-DOWN STRAPPING UP THROUGH THE STAKE POCKET AND BRING THE LONG END UP OVER THE LOAD. ASSURE THAT THE 2" HOLD-DOWN STRAP IS CENTERED ON THE 2" STRAPPING PAD AND THE STAKE POCKET. SLIDE ONE 2" STRAP SEAL DOWN OVER END OF STRAP PAD AS SHOWN AND CRIMP SEAL WITH ONE CRIMP. SLIDE ANOTHER 2" STRAP SEAL DOWN OVER SHORT END OF HOLD-DOWN STRAP AND DOUBLE CRIMP EACH SEAL. THIS METHOD MAY ONLY BE USED ON THE M1077 FLATRACK STAKE POCKETS DUE TO THE TRIANGULAR SHAPE OF THE M1 FLATRACK STAKE POCKETS.



OMITTED SLP PALLET UNIT ASSEMBLY

ONE OMITTED PALLETIZED UNIT ASSEMBLY IS REQUIRED FOR EACH OMITTED PALLET UNIT OF SEPARATE LOADING PROJECTILES WITHIN THE LOAD.